

# Small Construction Hammerhead Tower Crane QTZ4208 External Climbing Type

#### **Basic Information**

Place of Origin: China

Brand Name: AVITT or others

Certification: CE, ISO, GOST, CU-TR
 Model Number: QTZ40(4208) Tower Crane

Minimum Order Quantity: 1

• Price: \$24300-25900 per set

• Packaging Details: Naked packing, 3\*40'HQ containers.

• Delivery Time: 10 days after receiving the deposit or origin

LC

• Payment Terms: TT, LC

• Supply Ability: 40 sets per month



### **Product Specification**

Condition: 100% New

Application: Buildings And ProjectsType: Fixed With Tower Head

Max. Load: 4 T
 Jib Length: 42 M
 Tip. Load: 0.8 T

Power supply: 380V/50Hz, 415V/50Hz, 220V/50Hz Or

According To Clients Need

Mast section: 1.5\*1.5\*2.2mMain Chord: 140\*10mm

After Sale Service: Engineers Available To Service Overseas



#### **Product Description**

#### Small Construction Hammerhead Tower Crane QTZ4208 External Climbing Type

#### Main Technical Parameters QTZ4208 Hammerhead Tower Crane

1) Nominal Lifting Moment: 400KN.m

2) Working Range: 3-42m 3) Max. Lifting Capacity: 4t

4) Independent Standing Height: 29m 5) Attached Standard Height: 120m

6) Lifting Speed: 64.15/32.57/7.0, 32.14/15.60/3.5m/mim

7) Slewing Speed: 0.7/0.35r/min

8) Radius Changing Speed: 38.6/25.2m/mim

9) Climbing Speed: 0.4m/min

#### Specification of QTZ4208 Hammerhead Tower Crane

opecinication of a	124200 Hammerne	a rower orane
Model		QTZ40 (4208) Tower Crane
Working Radius (m)		42
Max. Load Capacity (T)		4
Tip Load (T)		0.8
Freestanding height (m)		29
Max. Height with anchorages (m)		120
Mast Section dimension (m)		1.5×1.5×2.2, angle steel 140×10mm
<b>Hoisting Mechanis</b>	Speed (m/min)	64.15/32.57/7.0, 32.14/15.60/3.5
	Motor power (kw)	15/15
Slewing Mechanism	Speed (r/min)	0.7/0.35
	Motor power (kw)	3.7
Trolleying Mechanism	Speed (m/min)	38.6/25.2
	Motor power (kw)	1.5/2.2
Jacking-up System	Speed (m/min)	0.4
	Motor power (kw)	4
Total Power (kw)		24.9
Power Supply		380V/50Hz, 415/50Hz, 220V/60Hz, ect

#### Feature of QTZ4208 Hammerhead Tower Crane

- a. Freestanding height is 29m and max. height 120m by adding mast sections and wall ties (anchorage).
- b. Equipped with all kinds of safety devices, like height limiter, radius limiter, load moment limiter, weight limiter, slewing limiter and ect.
- c. The famous three mechanisms which has steady working, high speed and efficiency.
- d. Foundation type: fixed with cross-beam, well-frame, outrigger or base with ballast

#### Pictures of QTZ4208 Hammerhead Tower Crane







## Jinan Avitt International Trade Co., Ltd-HYCM Tower Crane



0086-18254159408



emma1109@foxmail.com



hycmtowercrane.com

No.218-1,Building 8, Comprehensive Building, Zone 8, Dongshan Garden, Shuangshan Street, Zhangqiu District, Jinan City, Shandong Province, China