



QTZ50(5008) Fixed Tower Crane 50 Meters Jib Length Specifications

Our Product Introduction

Basic Information

- Place of Origin: China
- Brand Name: AVITT or others
- Certification: CE, ISO, GOST, CU-TR
- Model Number: QTZ50(5008) Tower Crane
- Minimum Order Quantity: 1
- Price: \$26600-28600 per set
- Packaging Details: Naked packing, 3*40'HQ containers.
- Delivery Time: 10 days after receiving the deposit or origin LC
- Payment Terms: TT, LC
- Supply Ability: 40 sets per month



Product Specification

- Condition: 100% New
- Application: Buildings And Projects
- Type: Fixed With Tower Head
- Max. Load: 4 T
- Jib Length: 50 M
- Tip. Load: 0.8 T
- Power supply: 380V/50Hz, 415V/50Hz, 220V/50Hz Or According To Clients Need
- Mast section: 1.6*1.6*2.2m
- Main Chord: 160*12mm
- After Sale Service: Engineers Available To Service Overseas



for more products please visit us on hycmtowercrane.com

Product Description

QTZ50(5008) Fixed Tower Crane 50 Meters Jib Length Specifications

Performance parameters of QTZ50 Fixed Tower Crane

This tower crane is an hammerhead with topkit head tower crane, includes foundation frame, mast sections (tower body), climbing system, slewing units, horizontal lifting jib / boom, counter-jib, tower head, operation cab, three mechanisms, electric system and safety device.

The max. Boom length is 50m which consist of every 6meters and minimum length is 30m

This tower crane freestanding height is 29m and max.height is 120m with more mast section and 6sets anchorages.

The max. Load capacity is 4t and tip load at the end jib is 0.8t.

Specification of QTZ50 Fixed Tower Crane

Rated Lifting Moment (KN.,)	500
Rated Loading Capacity (t)	5
Max. Lifting Load (t)	5
Tip Load (t)	0.8
Max. Lifting Height (m)	120
Freestanding height (m)	29
Rope length (m)	320
Span (m)	50
Working range (m)	3 to 50
Slewing speed (r/min)	0.6/0.3
Trolley speed (m/min)	38.6/25.5
Jacking-up speed (m/min)	0.4
Counter jib length (m)	12
Power supply	380V/50Hz or according to client's requirements
Power Capacity (kw)	24.9
Electric switch box	Schneider
Hoisting speed (m/min)	32.14/15.6/3.5 65.14/32.57/7.0
Main Material (mm)	160*10 /angle steel /Q235B
Mast section (m)	1.6*1.6*2.2

Overview of QTZ50 Fixed Tower Crane

1. This type Tower Cranes with the "top head" also called Topkit tower crane, Cat Head tower crane, Kit Top tower crane ect.
2. This Small tower crane or mini tower crane used for lower story buildings construction, normally 5-15 lays.
3. This crane can save time on other jobsite duties by easily moving materials from one place to another.
4. They can be used in conjunction with other tower cranes at sites where space is confined

Pictures of QTZ50 Fixed Tower Crane





Jinan Avitt International Trade Co., Ltd-HYCM Tower Crane



0086-18254159408



emma1109@foxmail.com



hycmtowercrane.com

No.218-1, Building 8, Comprehensive Building, Zone 8, Dongshan Garden, Shuangshan Street, Zhangqiu District, Jinan City, Shandong Province, China