



6 Tons Building Tower Crane Construction Safety Equipment For Sale

Our Product Introduction

Basic Information

- Place of Origin: China
- Brand Name: AVITT or others
- Certification: CE, ISO, GOST, CU-TR
- Model Number: QTZ63(5013) Crane Tower
- Minimum Order Quantity: 1
- Price: \$46000-49300 per set
- Packaging Details: Naked packing, 5*40'HQ containers.
- Delivery Time: 10 days after receiving the deposit or origin LC
- Payment Terms: TT, LC
- Supply Ability: 40 sets per month



Product Specification

- Condition: 100% New
- Application: Buildings And Projects
- Type: Fixed With Tower Head
- Max. Load: 6 T
- Jib Length: 50 M
- Tip. Load: 1.3 T
- Power supply: 380V/50Hz Or According To Client's Requirements
- Mast section: 1.6*1.6*2.5m (block Type)
- Electric Box: Schneider
- Power Supply: 380V/50Hz, 415V/50Hz, 220V/50Hz Or According To Clients Need

for more products please visit us on hycmtowercrane.com

Product Description

6 Tons Building Tower Crane Construction Safety Equipment For Sale

Description

The cranes are used extensively in construction and other industry to hoist and move materials.

This Tower Crane is so well thought out that you can maximize productivity from your investment without compromising on safety while in use, during maintenance, during erection and dismantling, or while being transported between sites.

Specification

Foundation	fixed or mobile
Free height	40 meters
Max. height	150 meters
Max. radius	50 meters
Jib end load	1.3 t
Max. load	6 T
Drum capacity	400 meters
Lifting speed	80/40/8.5 40/20/4.25m/min
Slewing speed	0.6 r/in
Trolley speed	40/20 m/min
Power line voltage	380V/50Hz (60Hz)
Counter weight	Stell-structured frame (without concrete)
Mast section	1.68 x 1.68 x 2.5 m or 1.6*1.6*2.5 m

Characteristics

- 1) QTZ63 tower crane is one of our key goods which have competitive price and excellent quality, suitable for all kinds of construction project and can work under all kinds of work condition.
- 2) This kind of crane adopts standard section hydraulic lifting and connecting, and can adjust the crane height according to the actual height of the building, and at the same time the lifting capacity will not be affected; The max. attached height can reach 150m.
- 3) It has high working speed, good speed-adjusting performance, steady operation and high efficiency. Three-speed motor and mono-speed ratio decelerator are applied in the lifting struction, which enables heavy load low speed and light load high speed.
The range-change structure drives the dolly to change range on the horizontal arm, with good positioning performance. Planet gear decelerator is applied in the circumgyrating structure, together with moment-limiting hydraulic coupler, which can relize high load capacity, steady starting and reliable operation.
- 4) The crane has complete set of safety devices, which can guarantee the safe and high efficienct operation of the equipment. The machine is equipped with lifting height limiter, dolly range-change limiter, moment limiter, weight limiter, circumgyrating limiter, etc.
- 5) The machine has scientific layout and beautiful appearance. The operator's room is set independently on one side, with good vision field. It creates a good working environment for the operator.

Pictures





Jinan Avitt International Trade Co., Ltd-HYCM Tower Crane



0086-18254159408



emma1109@foxmail.com



hycmtowercrane.com

No.218-1,Building 8, Comprehensive Building, Zone 8, Dongshan Garden, Shuangshan Street, Zhangqiu District, Jinan City, Shandong Province, China