

External Climbing Construction Cranes Tower QTZ 50 50m Boom Specification

Basic Information

- Place of Origin:
- Brand Name:
- Certification:
- Model Number:
- Minimum Order Quantity:
- Price:
- Packaging Details:
- Delivery Time:
- Payment Terms:
- Supply Ability:



Product Specification

Condition:	100% New	
 Application: 	Buildings And Projects	
• Туре:	Fixed With Tower Head	
Max. Load:	5 T	
 Jib Length: 	50 M	
• Tip. Load:	1.0 T	
 Power supply: 	380V/50Hz Or According To Client's Requirements	
 Mast section: 	1.5*1.5*2.5 M	

China

1

LC

TT, LC

AVITT or others

CE, ISO, GOST, CU-TR

\$32100-35200 per set

40 sets per month

containers.

QTZ50(5010) Tower Crane

Naked packing, 3*40'HQ+1*20'GP

10 days after receiving the deposit or origin



External Climbing Construction Cranes Tower QTZ 50 50m Boom Specification

Description

This series of tower crane, working ranging from 2.5m to 50m has a horizontal jib frame, a jib-trolley radius-changing mechanism and a hydraulic self-raising mechanism.

It is original in design, reliable in operation and satisfactory in shape. Equipped with all necessary safety devices, these cranes show a good speed-control capacity, satisfactory operating stability and high work efficiency.

They can be widely used for the construction of high-rise hotels, residential buildings, high-rise industrial buildings, large-span factory buildings and tower-like buildings like tall chimneys.

Specification

Model		QTZ50 (TC5010) Tower Crane
Туре		Fixed and external climbing type
Working Radius (m)		50
Max. Load Capacity (T)		5
Tip Load (T)		1.0
Freestanding height (m)		30
Max. Height with anchorage (m)		120
Mast Section dimension (m)		1.6×1.6×2.5, Square 135×10mm
Hoisting Mechanism	Speed (m/min)	(a=2) 64.15/32.57/7.0 (a=4) 32.14/15.60/3.5
	Motor power (kw)	15/15/4
Slewing Mechanism	Speed (r/min)	0.70/0.35
	Motor power (kw)	3.7*2
Trolleying Mechanism	Speed (m/min)	38.6/25.2
	Motor power (kw)	2.2/1.5
Jacking-up System	Speed (m/min)	0.4
	Motor power (kw)	4
Total Power (kw)		24.9
Power Supply		380V/50Hz or according to clients needs


Safety Features

- 1. Overload protection: If the material is over the capacity, the crane will give a sharp warning for protection itself
- 2. Emergency brake: If the operation staff encounter some emergency situation, we could start the emergency brake system to protection the related treasure.
- 3. Control Method: Room control or remote control to avoid any injure to the operation staff
- 4. Main lifting motor: with thermal protection and currency protection

Main markets for tower crane:

- 1. Middle East
- 2. Asia
- 3. Russia
- 4. South America
- 5. Oceania
- 6. North America

Loading Containers



0086-18254159408

emma1109@foxmail.com

e hycmtowercrane.com

No.218-1,Building 8, Comprehensive Building, Zone 8, Dongshan Garden, Shuangshan Street, Zhangqiu District, Jinan City, Shandong Province, China