

QTP160 Top Less Tower Crane 10 Tons Split Mast Tower Crain Price

Basic Information

- Place of Origin:
- Brand Name:
- Certification:
- Model Number:
- Minimum Order Quantity:
- Price:
- Packaging Details:
- Delivery Time:
- Payment Terms:
- Supply Ability:



Product Specification

Application:	Buildings And Projects
• Type:	Fixed With Tower Head
• Max. Load:	10 T
 Jib Length: 	60 M
• Tip. Load:	2.0 T
• Power supply:	380V/50Hz Or According To Client's Requirements
 Mast section: 	1.835*1.835*2.5m Or 2*2*3m (split Type)
Main Chord:	125*14mm Or 200*20mm

China HYCM

1

LC TT, LC

containers.

10 sets per month

CE, ISO, GOST, CU-TR

\$111200-117800 per set

QTZ160(PT6020) Tower Crane

Naked packing, 7*40'HQ or 8*40'HQ

25 days after receiving the deposit or origin



More Images



Product Description

QTP160 Top Less Tower Crane 10 Tons Split Mast Tower Crain Price

Description

QTP160(PT6020) Topless Tower Crane was a topless split tower crane, various performance indicators have reached international levels, the split mast sections all achieve impeller blasting, improve the surface hardness of steel, enhance the coating adhension, extend equipment useful life. Mast sections adopt split structure, convenient for transportation and storage, save the long distance freight, the main chord of mast section adopts Q345B materials, adaptability to environment. The mechanism adopt domestic famous factory products, reliable performance, good governing performance and shocklessness.

Our company employs 300 skillful personnel and is equipped with Panasonic professional robotic welding equipment, machining centers, large CNC gantry milling, CNC double-sided milling, CNC plasma cutting machines, computer-aided assembly line, fully automated spraying line and so on. Therefore, we can easily meet your requirements.

We are dedicated to the development and production of tower cranes, construction hoists, material hoists, suspended platforms and all relative accessories.

Specification

Туре	Topless or Flattop no head
Max. Lifting Load (t)	10
Tip Load (t)	2.0
Max. Lifting Height with anchorage (m)	200
Free standing height (m)	45-60
Rope length (m)	400
Span (m)	60
Working range (m)	3 to 60
Slewing speed (r/min)	0-0.6
Trolley peed (m/min)	0-60
Jacking-up speed (m/min)	0.4
Power supply	380V/50Hz or according to client's requirements
Power Capacity (KW)	61.5
Electric switch box	Schneider
Hoisting speed (m/min)	(a=2)0-80; (a=4)0-50
Mast section (m)	1.835*1.835*2.5 (125*14mm two angle steel with rib) Or 2×2×3, angle steel 200×20mm

Advantages

1. Modular design

2. Customised crane configuration

3. Pre-installed assemblies

4. Adjustable load capacity

- 5. Intelligent high-performance drives
- 6. Climbing outside or inside buildings
- 7. Safety monitoring during climbing
- 8. Top comfort for increased productivity

Photos



Jinan Avitt International Trade Co., Ltd-HYCM Tower Crane

0086-18254159408

emma1109@foxmail.com

e hycmtowercrane.com

No.218-1,Building 8, Comprehensive Building, Zone 8, Dongshan Garden, Shuangshan Street, Zhangqiu District, Jinan City, Shandong Province, China