



64M Tower Crane Boom Length Civil Construction Equipment 12 tons Topless Type

Our Product Introduction

for more products please visit us on hycmtowercrane.com

Basic Information

- Place of Origin: China
- Brand Name: HYCM
- Certification: CE, ISO, GOST, CU-TR
- Model Number: QTZ230(PT6425) Tower Crane
- Minimum Order Quantity: 1
- Price: \$134800-1436000 per set
- Packaging Details: Naked packing, 8*40;HQ containers.
- Delivery Time: 30 days after receiving the deposit or origin LC
- Payment Terms: TT, LC
- Supply Ability: 5 sets per month




Product Specification

- Condition: 100% New
- Application: Buildings And Projects
- Type: Fixed With Tower Head
- Max. Load: 12 T
- Jib Length: 64 M
- Tip. Load: 2.5 T
- Power supply: 380V/50Hz Or According To Client's Requirements
- Mast section: 2*2*3m
- Electric Box: Schneider
- Power Supply: 380V/50Hz, 415V/50Hz, 220V/50Hz Or According To Clients Need



More Images



Product Description

64M Tower Crane Boom Length Civil Construction Equipment 12 tons Topless Type

Description

For a fast and reliable crane with the technology to position even the heaviest load at the site with pinpoint precision, see our range of flat top cranes. This range is ideal for sites with height restrictions as well as in situations when available mobile cranes restrict the weight of the individual crane components, as the flat top crane's jib can be erected and dismantled piece by piece!

We offers an extensive range of flat top cranes spanning 400 to 2300tm which ensures that we can meet any lifting requirements.

15 Years of experience in a worldwide market ensures that all concerns are addressed in every design. For instance, wherever possible all cranes and components are designed to be packed into standard shipping containers, minimizing shipping costs. Likewise, speed and ease of erection are always taken into account.

All of our flat top cranes are built to the highest quality offering our full array of [features](#).

Specification

Rated Lifting Moment (KN.M)	2300
Rated Loading Capacity (t)	12
Max. Lifting Load (t)	12
Span (m)	64
Working range (m)	3 to 64
Tip Load (t)	2.5
Max. Lifting Height (m)	180
Free standing height (m)	50-60
Rope length (m)	500
Slewing speed (r/min)	0-0.6
Trolley peed (m/min)	0-60
Jacking-up speed (m/min)	0.4
Power supply	380V/50Hz or according to client's requirements
Power Capacity (kw)	61.5
Electric switch box	Schneider
Main Material (mm)	200*20 / angle steel
Mast section (m)	2*2*3 (split type)

The eight advantages about the flat-top crane

- 1.reduce the dismounting requirements, lower weight, low mounting height, dismount each mast at a time in the air, save the labor cost, safety and fast.
2. it is suitable for crossover work of the cranes, without the tower cap and pull rod, the safety will be increased when there need the crossover work.
3. It is suitable for the special requirement about the height, such as airport nearby, tunnel, workshop ,and the construction site with high-tension cable.
4. It is suitable for the construction site that has the requirement about the crane boom, it can be used as internal climbing crane in the high-rise buildings, irregular roof or small areas.
5. It is very convenient for dismounting in the restricted construction site, dismount each crane boom at a time by manual.
- 6.The steel structure of crane boom has long using life and high safety standard.
7. The crane boom is good applicability, high-usage,the design of the topless tower crane boom is easy for realizing the serialization and standardization. Reduce the design and making cost.
8. Low design cost, short cycle, can much better satisfy the multiple demands of the customers.

Pictures



emma1109@foxmail.com
0086 18254159408



Jinan Avitt International Trade Co., Ltd-HYCM Tower Crane



0086-18254159408



emma1109@foxmail.com



hycmtowercrane.com

No.218-1, Building 8, Comprehensive Building, Zone 8, Dongshan Garden, Shuangshan Street, Zhangqiu District, Jinan City, Shandong Province, China