



QTZ40 Telescopic Tower Crane Outer Climbing Construction Manual 4ton

Our Product Introduction

for more products please visit us on hycmtowercrane.com

Basic Information

- Place of Origin: China
- Brand Name: HYCM
- Certification: CE, ISO, GOST, CU-TR
- Model Number: QTZ40(4807) Tower Crane
- Minimum Order Quantity: 1
- Price: \$24900-26500 per set
- Packaging Details: Naked packing, 3*40'HQ containers.
- Delivery Time: 10 days after receiving the deposit or origin LC
- Payment Terms: TT, LC
- Supply Ability: 40 sets per month



Product Specification

- Condition: 100% New
- Application: Buildings And Projects
- Type: Fixed With Tower Head
- Max. Load: 4t
- Jib Length: 48m
- Tip. Load: 0. T
- Power supply: 380V/50Hz, 415V/50Hz, 220V/50Hz Or According To Clients Need
- Mast section: 1.5*1.5*2.2m
- Main Chord: 140*12mm
- After Sale Service: Engineers Available To Service Overseas



More Images



Product Description

QTZ40 Telescopic Tower Crane Outer Climbing Construction Manual 4ton

Quick Details of QTZ40 4807 Topkit Tower Crane

This tower crane is an hammerhead with topkit head tower crane, includes foundation frame, mast sections (tower body), climbing system, slewing units, horizontal lifting jib / boom, counter-jib, tower head, operation cab, three mechanisms, electric system and safety device.

The max. Boom length is 48m which consist of every 6meters and minimum length is 30m

This tower crane freestanding height is 29m and max.height is 120m with more mast section and 6sets anchorages.

The max. Load capacity is 4t and tip load at the end jib is 0.7t.

Specification of QTZ40 4807 Topkit Tower Crane

Rated Lifting Moment (KN.M)	400
Type	Fixed with tower head
Rated Loading Capacity (t)	4
Max. Lifting Load (t)	4
Tip Load (t)	0.7
Max. Lifting Height (m)	120
Free standing height (m)	29
Rope length (m)	320
Span (m)	48
Working range (m)	3 to 48
Slewing speed (r/min)	0.7/0.35
Trolley peed (m/min)	38.6/25.2
Jacking-up speed (m/min)	0.4
Counter jib length (m)	12.89
Power supply	380V/50Hz or according to client's requirements
Power Capacity (kw)	24.9
Electric switch box	Schneider
Hoisting speed (m/min)	(a=2) 64.15/32.57/7.0; (a=4) 32.14/15.60/3.5
Mast section (m)	1.5*1.5*2.2m (140*12 /angle steel /Q235B)

Safety devices:

- 1): hoist height limit
- 2): over speed limit
- 3)over load limit
- 4): lifting moment limit
- 5): slewing angle limit
- 6): emergency stop button
- 7): obstruction light (tip of jib, tower head)
- 8): wind lock device.





Jinan Avitt International Trade Co., Ltd-HYCM Tower Crane



0086-18254159408



emma1109@foxmail.com



hycmtowercrane.com

No.218-1,Building 8, Comprehensive Building, Zone 8, Dongshan Garden, Shuangshan Street, Zhangqiu District, Jinan City, Shandong Province, China