4 tons TC4810 Top Climbing Mini Tower Cranes 380v/50hz Power Civil Projects

Our Product Introduction

Basic Information

- Place of Origin: China
- Brand Name: HYCM
- Certification: CE, ISO, GOST, CU-TR
- Model Number: QTZ40(4810) Tower Crane
- Minimum Order Quantity: 1
- Price: $25400-26900 per set
- Packaging Details: Naked packing, 3*40'HQ containers.
- Delivery Time: 10 days after receiving the deposit or origin LC
- Payment Terms: TT, LC
- Supply Ability: 40 sets per month

Product Specification

- Condition: 100% New
- Application: Buildings And Projects
- Type: Fixed With Tower Head
- Max. Load: 4 T
- Jib Length: 48 M
- Tip. Load: 1.0 T
- Power supply: 380V/50Hz Or According To Client's Requirements
- Mast section: 1.5*1.5*2.2m
- Color: Yello, Red Or Others
- Main Chord: 160*12mm
- Highlight: **4 ton top climbing tower crane**, **TC4810 mini tower crane 380v**, **civil project topkit tower crane**

More Images

for more products please visit us on hycmtowercrane.com

Our Product Introduction

Product Description

4 tons TC4810 Top Climbing Mini Tower Cranes 380v/50hz Power Civil Projects

Shot introduction

1. Fixed Tower Cranes are fixed to the ground on a concrete base
2. The base is connected to the mast sections which offers the crane its height.
3. Further the mast section is attached to the slewing unit (lower slewing table, slewing bearing, upper slewing table and slewing body) that allows the crane to rotate.
4. The slewing unit is connected to three parts which are: horizontal jib / boom, shorter counter-jib, and tower cat.

Specification

Model	QTZ40 (4810)
Rated Loading Capacity (t)	4
Max. Lifting Load (t)	4
Tip Load (t)	1.0
Max. Lifting Height (m)	120
Freestanding height (m)	29
Rope length (m)	320
Span (m)	48
Working range (m)	3 to 48
Slewing speed (r/min)	0.7/0.35
Trolley peed (m/min)	38.6/25.2
Jacking-up speed (m/min)	0.4
Counter jib length (m)	12.89
Power supply	380V/50Hz or according to client's requirements
Power Capacity (kw)	24.9
Electric switch box	Schneider
Hoisting speed (m/min)	(a=2) 64.15/32.57/7.0; (a=4) 32.14/15.60/3.5
Main Material (mm)	160*12 /angle steel /Q235B
Mast section (m)	1.5*1.5*2.2
Optional parts (if you need them, please let me know in advance)	1)Anemometer 2)Air condition in cabin 3) Block box 4) Remote control 5) VFD control

Details:

1. Advanced technical parameters, max. Radius is 50m, the static height is 30m, it can reach up to max. height 120m by adding mast sections and anchorages.
2. Various tower crane types, such as stationary, external climbing and internal climbing types, is widely used in different construction sites.
3. Good speed adjusting performance, excellent stability.
4. Simple maintenance and reliable work.
5. Advanced electronic appliances, such as Schneider.
6. Equipped with excellent safety devices produced by world-class technology, including weight limiter, moment limiter, height limiter, radius limiter, slewing limiter, slewing and trolleying brakes.
7. Anti-broken wire rope device and anti-broken shaft device

for more products please visit us on hycmtowercrane.com

Jinan Avitt International Trade Co., Ltd-HYCM Tower Crane

0086 18254159408 emma1109@foxmail.com hycmtowercrane.com

No.218-1,Building 8, Comprehensive Building, Zone 8, Dongshan Garden, Shuangshan Street, Zhangqiu District, Jinan City, Shandong Province, China