qtz6010 Tower Crane Cat Hammer-Head Tower Kren 8T Capacity Quotation

Our Product Introduction

Basic Information

- Place of Origin: China
- Brand Name: HYCM
- Certification: CE, ISO, GOST, CU-TR
- Model Number: QTZ80(6010) Tower Crane
- Minimum Order Quantity: 1
- Price: $62400-66800 per set
- Packaging Details: Naked packing, 6*40'HQ containers.
- Delivery Time: 10 days after receiving the deposit or origin LC
- Payment Terms: TT, LC
- Supply Ability: 40 sets per month

Product Specification

- Condition: 100% New
- Application: Buildings And Projects
- Type: Fixed With Tower Head
- Max. Load: 8t
- Jib Length: 60m
- Tip. Load: 1.0t
- Power supply: 380V/50Hz Or According To Client's Requirements
- Mast section: 1.835*1.835*2.5m (blcok Type)
- Electric Box: Schneider
- Power Supply: 380V/50Hz, 415V/50Hz, 220V/50Hz Or According To Clients Need
- Highlight: **8T capacity tower crane**, **hammer-head tower kren**, **topkit tower crane with warranty**

More Images

for more products please visit us on hycmtowercrane.com

Our Product Introduction

for more products please visit us on hycmtowercrane.com

Product Description

qtz6010 Tower Crane Cat Hammer-Head Tower Kren 8T Capacity Quotation

Description

1) We are a professional manufacture of construction machine, have CE certification, with high quality and competitive price
2) Tower crane is a combination of advanced technologies from home and abroad, it is equipped with a hydraulic self-raising mechanism and frequency-converting slewing mechanism.
3) The crane has a complete set of safety devices, which can guarantee the safety and high efficient operation of the equipment, It is equipped with height limiter, moment limiter, radius-changing limiter and weight limiter, etc.
4) Our products have been exported to many countries and areas in Europe, America, Australia, the Middle East and Southeast Asia etc.

Specification

Rated Lifting Moment (KN.M)	800
Rated Loading Capacity (t)	8
Max. Lifting Load (t)	8
Tip Load (t)	1.0
Max. Lifting Height (m)	150
Free standing height (m)	45
Rope length (m)	400
Span (m)	60
Working range (m)	3 to 60
Slewing speed (r/min)	0.6
Trolley peed (m/min)	40/20
Jacking-up speed (m/min)	0.4
Counter jib length (m)	14.8
Power supply	380V/50Hz or according to client's requirements
Power Capacity (kw)	46.2
Electric switch box	Schneider
Main Material (mm)	135*12 /square steel
Mast section (m)	1.835*1.835*2.5

Feature&advantage

1. Suitable for all kinds of construction project and can work under all kinds of work condition.
2. It has high working speed, good speed-adjusting performance, steady operation and high efficiency.
3. The crane has complete set of safety devices, which can guarantee the safe and high efficient operation of the equipment.
4. Three-speed motor and mono-speed ratio decelerator are applied in the lifting structure, which enables heavy load low speed and light load high speed.
5. Planet gear decelerator is applied in the circumgyrating structure, together with moment-limiting hydraulic coupler, which can realize high load capacity, steady starting and reliable operation.

Pictures

Jinan Avitt International Trade Co., Ltd-HYCM Tower Crane

0086 18254159408 emma1109@foxmail.com hycmtowercrane.com

No.218-1,Building 8, Comprehensive Building, Zone 8, Dongshan Garden, Shuangshan Street, Zhangqiu District, Jinan City, Shandong Province, China