



Building qtz125 Tower Crane with VFD Control Undercarrige Foundation

Our Product Introduction

for more products please visit us on hycmtowercrane.com

Basic Information

- Place of Origin: China
- Brand Name: HYCM
- Certification: CE, ISO, GOST, CU-TR
- Model Number: QTZ125(6515) Tower Crane
- Minimum Order Quantity: 1
- Price: \$103000-116900 per set
- Packaging Details: Naked packing, 6*40'HQ or 7*40'HQ containers.
- Delivery Time: 20 days after receiving the deposit or origin LC
- Payment Terms: TT, LC
- Supply Ability: 20 sets per month



Product Specification

- Condition: 100% New
- Application: Buildings And Projects
- Type: Fixed With Tower Head
- Max. Load: 10 T
- Jib Length: 65 M
- Tip. Load: 1.5 T
- Power supply: 380V/50Hz Or According To Client's Requirements
- Mast section: 1.835*1.835*2.5m Or 2*2*3m
- Electric Box: Schneider
- Power Supply: 380V/50Hz, 415V/50Hz, 220V/50Hz Or According To Clients Need



More Images



Product Description

Building qtz125 Tower Crane with VFD Control Undercarriage Foundation

Features

- 1) Working Radius (m): 65
- 2) Max. Load Capacity (T): 10
- 3) Tip Load (T): 1.5
- 4) Mast Section dimension (m): 1.835×1.835×2.5 or 2*2*3m
- 5) Hoisting Mechanism Speed (m/min): 0-100 0-50
- 6) Motor power (kw): 45kw
- 7) Slewing Mechanism Speed (r/min): 0-0.6
- 8) Motor power (kw): 5.5×2
- 9) Trolleying Mechanism Speed (m/min): 0-60
- 10) Motor power (kw): 5.5

Specification

Model		QTZ125 (6515) Tower Crane
Working Radius (m)		65
Max. Load Capacity (T)		10
Tip Load (T)		1.5
Free standing height (m)		50
Max. Height with anchorages (m)		180
Mast Section dimension (m)		1.835×1.835×2.5, two angle steel with rib 125×12mm
Hoisting Mechanism	Speed (m/min)	0-100 0-50
	Motor power (kw)	45
Slewing Mechanism	Speed (r/min)	0-0.6
	Motor power (kw)	2*5.5
Trolleying Mechanism	Speed (m/min)	0-60
	Motor power (kw)	5.5
Jacking-up System	Speed (m/min)	0.4
	Motor power (kw)	5.5
Total Power (kw)		61.5
Power Supply		380V/50Hz, 220V/60Hz or others

Advantage

Automatic impeller blasting and spraying assembly line

Adopt the world first-class automatic spraying assembly line. The large structure parts are dealt with impeller blasting before spraying. That remove steel surface oxides and welding spatters effectively, eliminates the internal stress producing in welding process, increases the parts' anti-figure strength and steel surface hardness, increases painting adhesion and prolong the service life of the product maximizes efficiency and saves energy.

Strict quality examination

The strict quality test, raw material test, test of welding, checking welding quality of appearance, assembly and adjustment of jib, tower head and pivot in factory.

We have professional packing person to pack and put the tower crane in the container or on to the truck.

Pictures



Jinan Avitt International Trade Co., Ltd-HYCM Tower Crane



0086-18254159408



emma1109@foxmail.com



hycmtowercrane.com

No.218-1,Building 8, Comprehensive Building, Zone 8, Dongshan Garden, Shuangshan Street, Zhangqiu District, Jinan City, Shandong Province, China