



H3/36B 60m Types of Tower Crane Modle QTZ6036 12t Crantower Price For Sale

Our Product Introduction

for more products please visit us on hycmtowercrane.com

Basic Information

- Place of Origin: China
- Brand Name: HYCM
- Certification: CE, ISO, GOST, CU-TR
- Model Number: QTZ250(6030) Tower Crane
- Minimum Order Quantity: 1
- Price: \$151300-161200 per set
- Packaging Details: Naked packing, 9*40'HQ containers.
- Delivery Time: 20 days after receiving the deposit or origin LC
- Payment Terms: TT, LC
- Supply Ability: 10 sets per month



Product Specification

- Condition: 100% New
- Application: Buildings And Projects
- Type: Fixed With Tower Head
- Max. Load: 12t
- Jib Length: 60m
- Tip. Load: 3.6t
- Mast section: 2*2*3m (split Type)
- Electric Box: Schneider
- Power Supply: 380V/50Hz, 415V/50Hz, 220V/50Hz Or According To Clients Need
- Color: Yellow, Red Or According To Clients Needs



More Images



Product Description

H3/36B 60m Types of Tower Crane Modle QTZ6036 12t Crantower Price For Sale

Description

1. This series tower crane is characterized by horizontal jib frame, trolley travel, slewing self-climbing, novel structure and reliable running.
2. All accessories are adopted from home famous brands and electrical components from international famous brands.
3. "Quality First" is not just a slogan, which has already deeply rooted in ALCASS People's soul, besides we will also make all your purchases in unlimited satisfaction with star-rated after-sales services.

Specification

Model	H3/36B TC6036 Tower Crane	
Working Radius (m)	60	
Max. Load Capacity (T)	12	
Tip Load (T)	3.6	
Free standing height (m)	50	
Max. Height with anchorages (m)	180	
Mast Section dimension (m)	2×2×3, Angle steel 200×20mm	
Hoisting Mechanism	Speed (m/min)	0-100 0-50
	Motor power (kw)	45
Slewing Mechanism	Speed (r/min)	0-0.6
	Motor power (kw)	2*5.5
Trolleying Mechanism	Speed (m/min)	0-60
	Motor power (kw)	5.5
Jacking-up System	Speed (m/min)	0.4
	Motor power (kw)	5.5
Total Power (kw)	61.5	
Power Supply	380V/50Hz, 220V/60Hz or others	

Characteristics

- 1) Lifting multiplying factor switch-over which could achieve high speed for light load and low speed for heavy load.
- 2) Our tower sections are exchangeable, which provide our customers more conveniences.
- 3) We adopt to use Dual drawbars structure on lifting boom, which enables the lifting boom to be under no stress at lifting surface other than uniaxial stress, and moreover, it gets rid of the stress peak. It greatly improves the fatigue safety performance of lifting boom.
- 4) Adopts VVVF stepless speed variation device for lifting, radius changing and slewing mechanisms, to make sure it works steadily and effectively, it also lowers the maintenance cost.

Pictures





Jinan Avitt International Trade Co., Ltd-HYCM Tower Crane



0086-18254159408



emma1109@foxmail.com



hycmtowercrane.com

No.218-1,Building 8, Comprehensive Building, Zone 8, Dongshan Garden, Shuangshan Street, Zhangqiu District, Jinan City, Shandong Province, China