

# PT 5010 5T Hydraulic Telescopic Tower Crane Topless Flat Top Type Prices

## **Basic Information**

Place of Origin: ChinaBrand Name: HYCM

Certification: CE, ISO, GOST, CU-TR
 Model Number: QTZ50(PT5010) Tower Crane

Minimum Order Quantity:

• Price: \$37600-40900 per set

Packaging Details: Naked packing, 3\*40'HQ+1\*20'GP

containers.

• Delivery Time: 15 days after receiving the deposit or origin

LC

• Payment Terms: TT, LC

Supply Ability: 30 sets per month



## **Product Specification**

Application: Buildings And ProjectsType: Fixed With Tower Head

Max. Load: 5 T
 Jib Length: 50 M
 Tip. Load: 1.0 T

Power supply: 380V/50Hz Or According To Client's

Requirements

Mast section: 1.6\*1.6\*2.5 M (block Type)
Main Chord: 135\*10mm (square Tube)



## More Images





## **Product Description**

### PT 5010 5T Hydraulic Telescopic Tower Crane Topless Flat Top Type Prices

#### Performance parameters

- Max. jib length: 50m;
- · Max. lifting capacity: 5t;
- · Max. hoisting capacity at jib tip:1t;
- Rated lifting moment: 500 Kn.m;
- Max. freestanding height: 30m; Max. working height of anchored crane: 120m;

#### Specification

opecinication	•				
Rated lifting moment (kN.m)		500			
Lifting height (m)		Rope fall	Free-standing stationary crane		Anchored crane
		α2	30		120
		α 4	30		120
Working radius (m)		Max. working radius		50	
		Min. working radius		3	
Max. lifting capacity (t)		5			
Hoisting mechanism	Rope fall	α2		α 4	
	Speed (m/min)	65/32/7.0		32/16/3.5	
	Lifting weight (t)	1	2.5	2.5	5
	Power (kW)	15/15/4			
Tolleying mechanism		Speed (m/min)		0.7/0.35	
		Power (kW)		3.7	
Slewing mechanism		Speed (r/min)		0.4	
		Power (kW)		4	

#### **Technical features**

- a. Speeds of trolleying and slewing mechanisms are high, good speed adjusting performance, excellent stability.
- b. Anti-broken wire rope device and anti-broken shaft device
- c. Light structure, good stability, convenient transportation; Mast sections are SAW welding, safe and reliable. Advanced mechanisms, equipped with various safety devices, mechanical or Mechatronics products work in wretched conditions to keep tower cranes work well.
- d. Advanced electronic appliances, such as Schineider.
- e.. Equipped with excellent safety devices produced by world-class technology, including weight limiter, moment limiter, height limiter, radius limiter, slewing limiter, slewing and trolleying brakes.

#### **Main Parts**



Well Foundation (cross-beam, outrigger and base with ballast are also available)



0086-18254159408

emma1109@foxmail.com

hycmtowercrane.com

No.218-1,Building 8, Comprehensive Building, Zone 8, Dongshan Garden, Shuangshan Street, Zhangqiu District, Jinan City, Shandong Province, China