



Price of 6t Flattop Tower Kren Self Hydraulic Climbing Type Cranes

Our Product Introduction

for more products please visit us on hycmtowercrane.com

Basic Information

- Place of Origin: China
- Brand Name: HYCM
- Certification: CE, ISO, GOST, CU-TR
- Model Number: QTZ80(PT5515) Tower Crane
- Minimum Order Quantity: 1
- Price: \$65100-67500 per set
- Packaging Details: Naked packing, 6*40'HQ containers.
- Delivery Time: 20 days after receiving the deposit or origin LC
- Payment Terms: TT, LC
- Supply Ability: 30 sets per month



Product Specification

- Application: Buildings And Projects
- Type: Fixed With Tower Head
- Max. Load: 6t
- Jib Length: 55m
- Tip. Load: 1.5t
- Power supply: 380V/50Hz Or According To Client's Requirements
- Mast section: 1.835*1.835*2.5m (Block Type)
- Main Chord: 135*12mm (square Tube)



More Images



Product Description

Price of 6t Flattop Tower Kren Self Hydraulic Climbing Type Cranes

Description

This tower cranes are a modern form of balance crane that fixed to the ground on a concrete slab, tower cranes often give the best combination of height and lifting capacity and are used in the construction of tall buildings.

The base is then attached to the mast which gives the crane its height. Further the mast is attached to the slewing unit (gear and motor) that allows the crane to rotate.

On top of the slewing unit there are three main parts which are: the long horizontal jib (working arm), shorter counter-jib.

Specification

| | | |
|---------------------------------|---|---------------------------------|
| Model | QTZ80(PT5515) Topless Tower Crane | |
| Working Radius (m) | 55 | |
| Max. Load Capacity (T) | 6 | |
| Tip Load (T) | 1.5 | |
| Free standing height (m) | 40 | |
| Max. Height with anchorages (m) | 150 | |
| Mast Section dimension (m) | 1.833×1.833×2.5, square steel 135×12mm | |
| Hoisting Mechanism | Speed (m/min) | (a=2)80/40/8.5; (a=4)40/20/4.25 |
| | Motor power (kw) | 24/24/5.4 |
| Slewing Mechanism | Speed (r/min) | 0.6 |
| | Motor power (kw) | 2*3.7 |
| Trolleying Mechanism | Speed (m/min) | 40/20 |
| | Motor power (kw) | 3.3/2.2 |
| Jacking-up System | Speed (m/min) | 0.4 |
| | Motor power (kw) | 5.5 |
| Total Power (kw) | 34.8 | |

Feature

1. This Tower Cranes don't have the "head" of conventional cranes
2. This tower crane has a horizontal jib with hoisting mechanism, a jib-trolley radius-changing mechanism and a hydraulic self-raising mechanism.
3. It is original in design, reliable in operation and satisfactory in shape.
4. Equipped with all necessary safety devices
5. They can be widely used for the construction of high-rise hotels, residential buildings, high-rise industrial buildings, large-span factory buildings and tower-like buildings like tall chimneys.
6. They can also help you save time on other jobsite duties by easily moving materials from one area to another.

Photos





0086-18254159408



emma1109@foxmail.com



hycmtowercrane.com

No.218-1, Building 8, Comprehensive Building, Zone 8, Dongshan Garden, Shuangshan Street, Zhangqiu District, Jinan City, Shandong Province, China