



D5520 Telescopic Hydraulic Tower Crane 18T Luffing Building Materials

Our Product Introduction

for more products please visit us on hycmtowercrane.com

Basic Information

- Place of Origin: China
- Brand Name: HYCM, AVITT TOWER CRANE
- Certification: CE, ISO, GOST, CU-TR
- Model Number: QTD230(5520) Luffing Tower Crane
- Minimum Order Quantity: 1 set
- Price: \$179400-190900 per set
- Packaging Details: Naked packing, 10*40'HQ containers.
- Delivery Time: 30 days after receiving the deposit or origin LC
- Payment Terms: TT, LC
- Supply Ability: 5 sets per month



Product Specification

- Application: Buildings And Projects
- Type: Fixed With Tower Head
- Max. Load: 18t
- Jib Length: 55m
- Tip. Load: 2.0t
- Power supply: 380V/50Hz Or According To Client's Requirements
- Mast section: 2*2*3 M (split Type)
- Main Chord: 200*26 Mm (angle Steel)



More Images



Product Description

D5520 Telescopic Hydraulic Tower Crane 18T Luffing Building Materials

Performance parameters of D5520: performance parameters and technical indexes reach both domestic and international advanced level.

- Max. jib length: 55m;
- Max. lifting capacity 18t;
- Max. hoisting capacity at jib tip: 2.0t;
- Rated lifting moment: 2300 Kn.m;
- Max. freestanding height: 51m; Max. working height of anchored crane: 160m;

The Advantages

1. the large_scale luffing tower crane is equipped with heavy main hoisting system. Big lifting capacity.
2. The crane can climb following the the building structure due to the use of special climbing system. The lifting height has increased largely.
3. Big rolling angle of the crane boom, small rear turning radius ,suitable for the small construction site.
4. Suitable for the crossover work of the cranes.
5. Good performance of the boom combination, can realize the multiple working range.
6. The machine is equipped with the safety monitoring system. Display the the working conditions of the cranes all the time.

Specification

Model	QTD230(5520) Luffing Jib Tower Crane
Rated Lifting Moment (KN.M)	2300
Max. Lifting Load (t)	18
Tip Load (t)	2.0
Max. Lifting Height (m)	260
Free standing height (m)	65
Span (m)	55
Working range (m)	5 to 55
Slewing speed (r/min)	0-0.57
Trolley peed (m/min)	0-10
Jacking-up speed (m/min)	0.4
Power supply	380V/50Hz or according to client's requirements
Power Capacity (kw)	138
Electric switch box	Schneider
Hoisting speed (m/min)	(a=2) 0-72; (a=4) 0-36
Mast section (m)	2*2*3 (200*26mm /angle steel)

Commercial Terms

Price: Negotiable

Delivery time: 15-30 days after receiving 30% advanced payment

Trade terms: FOB (qingdao), CFR or CIF according to Clients needs

Terms of Payment: T/T or L/C (30% advanced payment, 70% before shipment)

Packing: Standard Exporting Packing

Warranty: At least 12 months

Photos





Jinan Avitt International Trade Co., Ltd-HYCM Tower Crane



0086-18254159408



emma1109@foxmail.com



hycmtowercrane.com

No.218-1,Building 8, Comprehensive Building, Zone 8, Dongshan Garden, Shuangshan Street, Zhangqiu
District, Jinan City, Shandong Province, China