



1.0 Tons Construction Material Hoist With Low Speed 0-36 m/min VFD Control

Our Product Introduction

for more products please visit us on hycmtowercrane.com

Basic Information

- Place of Origin: China
- Brand Name: HYCM or XINGDAO
- Certification: CE, ISO
- Model Number: SC Building Hoist
- Minimum Order Quantity: 1 set
- Price: \$21500-22800 per set
- Packaging Details: Naked packing, 1*40'HQ containers.
- Delivery Time: 15 days after receiving the deposit or origin LC
- Payment Terms: Western Union, L/C, T/T
- Supply Ability: 40 sets per month



Product Specification

- Condition: 100% New
- Application: Buildings And Projects
- Type: Electric Cable Climbing
- Max. Load: 1 T
- Max. Height: 150-200 M
- Rated Speed: 0-36 M/min
- Power supply: 380V/50Hz Or According To Client's Requirements
- Motor Power: 2*11 Kw
- Motor Brand: Taichang, Jinnuoi Or Other
- Mast Section Size: 650*650*1508mm



More Images



Product Description

1.0 Tons Construction Material Hoist With Low Speed 0-36 m/min VFD Control

Simple parameter

Model: SC100 Single cage construction hoist
 Rated load: 1000kg (1ton)
 Rated passengers: 10
 Motor power: 2*11kw
 Rated lifting speed: 0-36 m/min
 Mast section size: 0.65*0.65*1.508m or 0.8*0.8*1.508m
 Cage size: 3*1.3*2.3m or according to clients needs
 Power supply: 380V/50Hz, 220V/60Hz or others
 Max. Lifting height: 150m-200m
 With all standard accessories

Specification

Model	SC100 single cage construction hoist
Payload capacity	Up to 1000 kg
Speed	0-36m/min
Max. lifting height	150-200 m (Increased lifting height on request.)
Cage width (internal)	1.3 m & 1.5 m
Cage length (internal)	3 m
Cage height (internal)	2.2 m
Motor control	Directly driven without inverter
Motor power	2x11 kw
Power supply range	380V, 50Hz or 60 Hz, 3 phase
Type of mast	650mm, Tubular steel with integrated rack
Length mast section	1.508 m
Weight mast section with 1 racks	127 kg

Parts

1. Driver Cabin

The driver cabin of our construction hoist is constructed from hot dip galvanized plates with surface powder spraying treatment which ensure superior corrosion resistance. It has fan that can improve driver's working environment.

2. Gear Train

The new back gear is lengthened by one time at the stationary bearing end where it is equipped with locating taper pin to improve stress state and avoid loosening of back gear that will affect gear backlash.

The parts such as bear gear, idler wheel, etc. that have influence on running stability are improved to enhance machining and manufacturing precision. All of them will experience thermal refining treatment and galvanizing treatment after that, thus showing excellent durability. Case door pulley and cable pulley are made from nylon material which can prolong their life time and effectively reduce noise.

Picture





0086-18254159408



emma1109@foxmail.com



hycmtowercrane.com

No.218-1,Building 8, Comprehensive Building, Zone 8, Dongshan Garden, Shuangshan Street, Zhangqiu
District, Jinan City, Shandong Province, China