

QTZ40 Hydraulic Telescopic Hammerhead Tower Crane Specification TC4208

Basic Information

Place of Origin: ChinaBrand Name: HYCM

Certification: CE, ISO, GOST, CU-TR
Model Number: QTZ40(4208) Tower Crane

Minimum Order Quantity:

• Price: \$25600-27200 per set

Packaging Details: Naked packing, 3*40'HQ containers.

• Delivery Time: 10 days after receiving the deposit or origin

LC

• Payment Terms: TT, LC

Supply Ability: 40 sets per month



Product Specification

• Condition: 100% New

Application: Buildings And ProjectsType: Fixed With Tower Head

Max. Load: 4 T
Jib Length: 42 M
Tip. Load: 0.8 T

Power supply: 380V/50Hz, 415V/50Hz, 220V/50Hz Or

According To Clients Need

Mast section: 1.5*1.5*2.2mMain Chord: 140*10mm

After Sale Service: Engineers Available To Service Overseas



More Images



QTZ40 Hydraulic Telescopic Hammerhead Tower Crane Specification TC4208

Main Technical Parameters

1) Nominal Lifting Moment: 400KN.m

2) Working Range: 3-42m3) Max. Lifting Capacity: 4t

4) Independent Standing Height: 29m

5) Attached Standard Height: 120m 6) Lifting Speed: 64.15/32.57/7.0, 32.14/15.60/3.5m/mim

7) Slewing Speed: 0.7/0.35r/min

8) Radius Changing Speed: 38.6/25.2m/mim

9) Climbing Speed: 0.4m/min

Specification

Specification		
Model		QTZ40 (4208) Tower Crane
Working Radius (m)		42
Max. Load Capacity (T)		4
Tip Load (T)		0.8
Freestanding height (m)		29
Max. Height with anchorages (m)		120
Mast Section dimension (m)		1.5×1.5×2.2, angle steel 140×10mm
Hoisting Mechanis Speed (m/min)		64.15/32.57/7.0, 32.14/15.60/3.5
	Motor power (kw)	15/15
Slewing Mechanism	Speed (r/min)	0.7/0.35
	Motor power (kw)	3.7
Trolleying Mechanism	Speed (m/min)	38.6/25.2
	Motor power (kw)	1.5/2.2
Jacking-up System	Speed (m/min)	0.4
	Motor power (kw)	4
Total Power (kw)		24.9
Power Supply		380V/50Hz, 415/50Hz, 220V/60Hz, ect

- 1) We are a professional manufacture of construction machineS, have ISO, CE , GOST certification, high quality and competitive price
- 2) Tower crane is a combination of advanced technologies from home and abroad, it is equipped with a hydraulic self-raising mechanism and frequency-converting slewing mechanism.
- 3) The crane has a complete set of safety devices, which can guarantee the safety and high efficient operation of the equipment, It is equipped with height limiter, moment limiter, radius-changing limiter and weight limiter, etc.
- 4) Our products have been exported to many countries and areas in Europe, America, Australia, the Middle East and Southeast Asia etc.

Pictures







Jinan Avitt International Trade Co., Ltd-HYCM Tower Crane

0086-18254159408

emma1109@foxmail.com

hycmtowercrane.com

No.218-1,Building 8, Comprehensive Building, Zone 8, Dongshan Garden, Shuangshan Street, Zhangqiu District, Jinan City, Shandong Province, China