



TC4810 Self Raising Fixed Tower Crane QTZ40 4T Building Topkit Towercrane

Our Product Introduction

for more products please visit us on hycmtowercrane.com

Basic Information

- Place of Origin: China
- Brand Name: HYCM
- Certification: CE, ISO, GOST, CU-TR
- Model Number: QTZ40(4810) Tower Crane
- Minimum Order Quantity: 1
- Price: \$26800-28500 per set
- Packaging Details: Naked packing, 3*40'HQ containers.
- Delivery Time: 10 days after receiving the deposit or origin LC
- Payment Terms: TT, LC
- Supply Ability: 40 sets per month



Product Specification

- Condition: 100% New
- Application: Buildings And Projects
- Type: Fixed With Tower Head
- Max. Load: 4 T
- Jib Length: 48 M
- Tip. Load: 1.0 T
- Power supply: 380V/50Hz Or According To Client's Requirements
- Mast section: 1.5*1.5*2.2 M
- Color: Yello, Red Or Others
- Main Chord: 160*12 Mm



More Images



Product Description

TC4810 Self Raising Fixed Tower Crane QTZ40 4T Building Topkit Towercrane

Shot introduction

QTZ4810 Hammerhead tower crane for sale
 Fixed / stationary / anchored tower crane
 Max. load: 4ton
 Tip load: 1.0ton
 Jib length: 48m
 CE, ISO, GOST, CU-TR certificate

Specification

Rated Lifting Moment (KN.M)	400
Type	Fixed with tower head
Rated Loading Capacity (t)	4
Max. Lifting Load (t)	4
Tip Load (t)	1.0
Max. Lifting Height (m)	120
Free standing height (m)	29
Rope length (m)	320
Span (m)	48
Working range (m)	3 to 48
Slewing speed (r/min)	0.7/0.35
Trolley speed (m/min)	38.6/25.2
Jacking-up speed (m/min)	0.4
Counter jib length (m)	12.89
Power supply	380V/50Hz or according to client's requirements
Power Capacity (kw)	24.9
Electric switch box	Schneider
Hoisting speed (m/min)	(a=2) 64.15/32.57/7.0; (a=4) 32.14/15.60/3.5
Mast section (m)	1.5*1.5*2.2m (140*12 /angle steel /Q235B)

Details:

1. Advanced technical parameters, max. Radius is 50m, the static height is 30m, it can reach up to max. height 120m by adding mast sections and anchorages.
2. Various tower crane types, such as stationary, external climbing and internal climbing types, is widely used in different construction sites.
3. Good speed adjusting performance, excellent stability.
4. Simple maintenance and reliable work.
5. Advanced electronic appliances, such as Schneider.
6. Equipped with excellent safety devices produced by world-class technology, including weight limiter, moment limiter, height limiter, radius limiter, slewing limiter, slewing and trolleying brakes.
7. Anti-broken wire rope device and anti-broken shaft device





Jinan Avitt International Trade Co., Ltd-HYCM Tower Crane



0086-18254159408



emma1109@foxmail.com



hycmtowercrane.com

No.218-1, Building 8, Comprehensive Building, Zone 8, Dongshan Garden, Shuangshan Street, Zhangqiu District, Jinan City, Shandong Province, China