

Offer QTZ5011 Types of Tower Cranes with 4 tons and Well Frame **Foundation**

Basic Information

- Place of Origin:
- Brand Name:
- Certification:
- Model Number:
- Minimum Order Quantity:
- Price:
- Packaging Details:
- Delivery Time:
- Payment Terms:
- Supply Ability:



Product Specification

| Condition: | 100% New | |
|-----------------------------------|--|--|
| Application: | Buildings And Projects | |
| • Туре: | Fixed With Tower Head | |
| • Max. Load: | 4 T | |
| Jib Length: | 50 M | |
| • Tip. Load: | 1.1 T | |
| Power supply: | 380V/50Hz Or According To Client's Requirements | |
| Mast section: | 1.6*1.6*2.5m (blcok Type) | |
| Electric Box: | Schneider | |
| Power Supply: | 380V/50Hz, 415V/50Hz, 220V/50Hz C | |

According To Clients Need

China HYCM

1

LC TT, LC

CE, ISO, GOST, CU-TR

\$35400-36900 per set

40 sets per month

containers.

QTZ63(5011) Tower Crane

Naked packing, 3*40'HQ+1*20'GP

10 days after receiving the deposit or origin



Power Supply:

More Images



Product Description

Offer QTZ5011 Types of Tower Cranes with 4 tons and Well Frame Foundation

Description

1. Equipped with all kinds of safety devices, including height limiter, radius limiter, load moment limiter, weight limiter and grip block.

2. The tower crane has steady working, high speed and efficiency.

3. Slewing mechanism works together with motor, planet gear speed reducer and slewing arrester for better bearing capacity and steady operation

Specification

| N.A. 1.1 | | |
|---------------------------------|------------------|-------------------------------------|
| Model | | QTZ63 (5011) Tower Crane |
| Working Radius (m) | | 50 |
| Max. Load Capacity (T) | | 4 |
| Tip Load (T) | | 1.1 |
| Freestanding height (m) | | 30 |
| Max. Height with anchorages (m) | | 150 |
| Mast Section dimension (m) | | 1.6×1.6×2.5, square tube 135×10mm |
| Hoisting Mechanis Speed (m/min) | | 70/35/7.0, 35/17/3.5 |
| | Motor power (kw) | 18/18/5 |
| Slewing Mechanism | Speed (r/min) | 0.7/0.35 |
| | Motor power (kw) | 2*3.7 |
| Trolleying Mechanism | Speed (m/min) | 38.6/25.2 |
| | Motor power (kw) | 1.5/2.2 |
| Jacking-up System | Speed (m/min) | 0.4 |
| | Motor power (kw) | 4 |
| Total Power (kw) | | 24.9 |
| Power Supply | | 380V/50Hz, 415/50Hz, 220V/60Hz, ect |

Main features

This tower crane, has a horizontal jib frame, a jib-trolley radius-changing mechanism and a hydraulic self-raising mechanism. It is original in design, reliable in operation and satisfactory in shape.

Equipped with all necessary safety devices, these cranes show a good speed-control capacity, satisfactory operating stability and high work efficiency.

They can be widely used for the construction of high-rise hotels, residential buildings, high-rise industrial buildings, large-span factory buildings and tower-like buildings like tall chimneys.



No.218-1,Building 8, Comprehensive Building, Zone 8, Dongshan Garden, Shuangshan Street, Zhangqiu District, Jinan City, Shandong Province, China