

5013 External Climbing Type QTZ63 Manual Tower Crane CE Certificate in India

Basic Information

Place of Origin: ChinaBrand Name: HYCM

Certification: CE, ISO, GOST, CU-TR
Model Number: QTZ63(5013) Crane

Minimum Order Quantity:

• Price: \$50000-51900 per set

Packaging Details: Naked packing, 5*40'HQ containers.

Delivery Time:
10 days after receiving the deposit or origin

LC

Payment Terms: TT, LC

Supply Ability: 40 sets per month



Product Specification

Condition: 100% New

Application: Buildings And ProjectsType: Fixed With Tower Head

Max. Load: 6 TJib Length: 50 MTip. Load: 1.3 T

Power supply: 380V/50Hz Or According To Client's

Requirements

• Mast section: 1.6*1.6*2.5m (blcok Type)

Electric Box: Schneider

• Power Supply: 380V/50Hz, 415V/50Hz, 220V/50Hz Or

According To Clients Need

• Highlight: QTZ63 manual tower crane,

external climbing tower crane, CE certified topkit crane



More Images





Product Description

5013 External Climbing Type QTZ63 Manual Tower Crane CE Certificate in India

Main Technical Parameters

1) Nominal Lifting Moment: 630KN.m

2) Working Range: 3-50m 3) Max. Lifting Capacity: 6t

4) Independent Standing Height: 40m 5) Attached Standard Height: 150m 6) Lifting Speed: 80/40/8.5 40/20/4.25 m/mim

7) Slewing Speed: 0.6r/min

8) Radius Changing Speed: 40/20m/mim

Specification

Foundation	fixed or mobile
Free height	40 meters
Max. height	150 meters
Max. radius	50 meters
Jib end load	1.3 t
Max. load	6 T
Drum capacity	400 meters
Lifting speed	80/40/8.5 40/20/4.25m/min
Slewing speed	0.6 r/in
Trolley speed	40/20 m/min
Power line voltage	380V/50Hz (60Hz)
Counter weight	Stell-structured frame (without concrete)
Mast section	1.68 x 1.68 x 2.5 m or 1.6*1.6*2.5 m

Main features

This tower crane, has a horizontal jib frame, a jib-trolley radius-changing mechanism and a hydraulic self-raising mechanism. It is original in design, reliable in operation and satisfactory in shape.

Equipped with all necessary safety devices, these cranes show a good speed-control capacity, satisfactory operating stability and high work efficiency.

They can be widely used for the construction of high-rise hotels, residential buildings, high-rise industrial buildings, large-span factory buildings and tower-like buildings like tall chimneys.

Pictures





Jinan Avitt International Trade Co., Ltd-HYCM Tower Crane



0086-18254159408



emma1109@foxmail.com



e hycmtowercrane.com