



8T Specifications QTZ80(5513) Manual Tower Crane Construction Cranes Tower

Our Product Introduction

for more products please visit us on hycmtowercrane.com

Basic Information

- Place of Origin: China
- Brand Name: HYCM
- Certification: CE, ISO, GOST, CU-TR
- Model Number: QTZ80(5513) Tower Crane
- Minimum Order Quantity: 1
- Price: \$63600-65900 per set
- Packaging Details: Naked packing, 5*40'HQ containers.
- Delivery Time: 10 days after receiving the deposit or origin LC
- Payment Terms: TT, LC
- Supply Ability: 40 sets per month



Product Specification

- Condition: 100% New
- Application: Buildings And Projects
- Type: Fixed With Tower Head
- Max. Load: 8 T
- Jib Length: 55 M
- Tip. Load: 1.3 T
- Power supply: 380V/50Hz Or According To Client's Requirements
- Mast section: 1.833*1.833*2.5 M (blcok Type)
- Electric Box: Schneider
- Power Supply: 380V/50Hz, 415V/50Hz, 220V/50Hz Or According To Clients Need



More Images



Product Description

8T Specifications QTZ80(5513) Manual Tower Crane Construction Cranes Tower

Description

1. External climbing tower cranes are a modern form of balance crane that fixed to the ground on a concrete slab (and sometimes attached to the sides of structures),
2. Tower cranes often give the best combination of height and lifting capacity and are used in the construction of tall buildings.
3. The base is then attached to the mast which gives the crane its height. Further the mast is attached to the slewing unit (gear and motor) that allows the crane to rotate.
4. On top of the slewing unit there are three main parts which are: the long horizontal jib (working arm), shorter counter-jib, and the tower head.

Specification

Model		QTZ80(5513) Tower Crane
Working Radius (m)		55
Max. Load Capacity (T)		8
Tip Load (T)		1.3
Free standing height (m)		45
Max. Height with anchorages (m)		150
Mast Section dimension (m)		1.833×1.833×2.5, square steel 135×12mm
Hoisting Mechanism	Speed (m/min)	80/40/8.5 40/20/4.25
	Motor power (kw)	30/30
Slewing Mechanism	Speed (r/min)	0.6
	Motor power (kw)	2*3.7
Trolleying Mechanism	Speed (m/min)	40/20
	Motor power (kw)	3.3/2.2
Jacking-up System	Speed (m/min)	0.4
	Motor power (kw)	5.5
Total Power (kw)		46.2
Power Supply		380V/50Hz

Advantage

1. 15 years of experience in supplying new tower cranes.
2. Export to more than 20 countries with CE/ISO/GOST/CU-TR Certificates.
3. Mobile and internal climbing type tower cranes are also available.
4. Impeller blasting and rust protection painting with advanced painting process.
5. Strict and experience welding line
6. New designed mast, can be used to Internal and external climbing tower crane
7. Well known brand mechanism system, Schneider Electronic control system, Jjiangte or Jiuhe motor
8. Engineers available to service machinery overseas.
9. For warranty: 12 months from the B/L date.

What's more, some free easy worn spare parts are provided together with the crane.

Pictures



emma1109@foxmail.com
0086 18254159408



Jinan Avitt International Trade Co., Ltd-HYCM Tower Crane



0086-18254159408



emma1109@foxmail.com



hycmtowercrane.com

No.218-1,Building 8, Comprehensive Building, Zone 8, Dongshan Garden, Shuangshan Street, Zhangqiu District, Jinan City, Shandong Province, China