



Chinese Kind of TC6010 60 Meter Jib Tower Crane Fixed and Climbing Type

Our Product Introduction

for more products please visit us on hycmtowercrane.com

Basic Information

- Place of Origin: China
- Brand Name: HYCM
- Certification: CE, ISO, GOST, CU-TR
- Model Number: QTZ80(6010) Tower Crane
- Minimum Order Quantity: 1
- Price: \$68500-71500 per set
- Packaging Details: Naked packing, 6*40'HQ containers.
- Delivery Time: 10 days after receiving the deposit or origin LC
- Payment Terms: TT, LC
- Supply Ability: 40 sets per month



Product Specification

- Condition: 100% New
- Application: Buildings And Projects
- Type: Fixed With Tower Head
- Max. Load: 8 T
- Jib Length: 60 M
- Tip. Load: 1.0 T
- Power supply: 380V/50Hz Or According To Client's Requirements
- Mast section: 1.835*1.835*2.5 M (block Type)
- Electric Box: Schneider
- Power Supply: 380V/50Hz, 415V/50Hz, 220V/50Hz Or According To Clients Need



More Images



Product Description

Chinese Kind of TC6010 60 Meter Jib Tower Crane Fixed and Climbing Type

Description

- 1) We are a professional manufacture of construction machine, have CE certification, with high quality and competitive price
- 2) Tower crane is a combination of advanced technologies from home and abroad, it is equipped with a hydraulic self-raising mechanism and frequency-converting slewing mechanism.
- 3) The crane has a complete set of safety devices, which can guarantee the safety and high efficient operation of the equipment, It is equipped with height limiter, moment limiter, radius-changing limiter and weight limiter, etc.
- 4) Our products have been exported to many countries and areas in Europe, America, Australia, the Middle East and Southeast Asia etc.

Specification

Rated Lifting Moment (KN.M)	800
Rated Loading Capacity (t)	8
Max. Lifting Load (t)	8
Tip Load (t)	1.0
Max. Lifting Height (m)	150
Free standing height (m)	45
Rope length (m)	400
Span (m)	60
Working range (m)	3 to 60
Slewing speed (r/min)	0.6
Trolley speed (m/min)	40/20
Jacking-up speed (m/min)	0.4
Counter jib length (m)	14.8
Power supply	380V/50Hz or according to client's requirements
Power Capacity (kw)	46.2
Electric switch box	Schneider
Main Material (mm)	135*12 /square steel
Mast section (m)	1.835*1.835*2.5

Features

Hoisting Mechanism

The construction tower crane uses a large-size winding drum and the motor with three kinds of speed or with variable frequency system.

Slewing Mechanism

The continuously variable frequency speed regulation helps the balance crane to work with stable starting and braking as well as fast and accurate positioning. Therefore, our tower crane becomes the leading one in terms of performance and operability at home and abroad.

Trolling Mechanism

Adopting variable frequency speed regulation so that it works stably with little impact.

Pictures





Jinan Avitt International Trade Co., Ltd-HYCM Tower Crane



0086-18254159408



emma1109@foxmail.com



hycmtowercrane.com

No.218-1, Building 8, Comprehensive Building, Zone 8, Dongshan Garden, Shuangshan Street, Zhangqiu District, Jinan City, Shandong Province, China