



Construction Cranes Tower Quotation Specification QTZ 5010 4t Max. Load

Our Product Introduction

Basic Information

- Place of Origin: China
- Brand Name: HYCM
- Certification: CE, ISO, GOST, CU-TR
- Model Number: QTZ50(5010) Tower Crane
- Minimum Order Quantity: 1
- Price: \$33400-34000 per set
- Packaging Details: Naked packing, 3*40'HQ+1*20'GP containers.
- Delivery Time: 10 days after receiving the deposit or origin LC
- Payment Terms: TT, LC
- Supply Ability: 40 sets per month



Product Specification

- Condition: 100% New
- Application: Buildings And Projects
- Type: Fixed With Tower Head
- Max. Load: 4 T
- Jib Length: 50 M
- Tip. Load: 1.0 T
- Power supply: 380V/50Hz, 220V/60Hz Or According To Clients Needs
- Mast section: 1.6*1.6*2.5 M
- Main Chord: 135*10 Mm (square Tube)



More Images



for more products please visit us on hycmtowercrane.com

Product Description

Construction Cranes Tower Quotation Specification QTZ 5010 4t Max. Load

We value our customers; We value our customers' customers

HYCM-TOWER CRANE Focus on superior products (tower crane) and perfect service

Performance parameters

- a. Max. jib length: 50m
- b. Max. lifting capacity: 4t
- c. Max. hoisting capacity at jib tip: 1.0t
- d. Max. lifting moment: 500 t.m
- e. Max. free-standing height: 30m
- f. Max. working height of anchored crane: 120m
- g. Types of tower crane: fixed with outer side climbing type / inner climbing type and mobile type

Specification

Model	QTZ50 (5010) Tower Crane	
Type	Topkit / Cat Head	
Working Radius (m)	50	
Max. Load Capacity (T)	4	
Tip Load (T)	1.0	
Freestanding height (m)	29	
Max. Height with anchorage (m)	120	
Mast Section dimension (m)	1.6×1.6×2.5, Square 135×10mm	
Hoisting Mechanism	Speed (m/min)	(a=2) 64.15/32.57/7.0 (a=4) 32.14/15.60/3.5
	Motor power (kw)	15/15/4
Slewing Mechanism	Speed (r/min)	0.70/0.35
	Motor power (kw)	3.7
Trolleying Mechanism	Speed (m/min)	38.6/25.2
	Motor power (kw)	2.2/1.5
Jacking-up System	Speed (m/min)	0.4
	Motor power (kw)	4
Total Power (kw)	24.9	
Power Supply	380V/50Hz or according to clients needs	

Advantage

Automatic impeller blasting and spraying assembly line

Adopt the world first-class automatic spraying assembly line. The large structure parts are dealt with impeller blasting before spraying. That remove steel surface oxides and welding spatters effectively, eliminates the internal stress producing in welding process, increases the parts' anti-figure strength and steel surface hardness, increases painting adhesion and prolong the service life of the product maximizes efficiency and saves energy.

Strict quality examination

The strict quality test, raw material test, test of welding, checking welding quality of appearance, assembly and adjustment of jib, tower head and pivot in factory.

We have professional packing person to pack and put the tower crane in the container or on to the truck.

Our Service

-----Quality Assurance

Good quality is assured by advanced manufacturing technology. And all products will be checked by our quality-control manager.

-----Excellent Package

We provide standard, strong, protective package for our products to prevent it from outer damage.

-----Warranty Assurance

For our tower crane, we provide 1 year warranty period and quick replace service.

-----The Fastest Reply

Detailed information, specific model and price of products will be provided quickly after receiving inquiry.

Photos



Jinan Avitt International Trade Co., Ltd-HYCM Tower Crane



0086-18254159408



emma1109@foxmail.com



hycmtowercrane.com

No.218-1, Building 8, Comprehensive Building, Zone 8, Dongshan Garden, Shuangshan Street, Zhangqiu District, Jinan City, Shandong Province, China