8T QTZ6012 Power Cable Kind Of Tower Cranes 60 meter Quotation Building Kren

Our Product Introduction

Basic Information

- Place of Origin: China
- Brand Name: HYCM
- Certification: CE, ISO, GOST, CU-TR
- Model Number: QTZ100(6012) Tower Crane
- Minimum Order Quantity: 1
- Price: $68300-72500 per set
- Packaging Details: Naked packing, 6*40'HQ containers.
- Delivery Time: 20 days after receiving the deposit or origin LC
- Payment Terms: TT, LC
- Supply Ability: 20 sets per month

Product Specification

- Condition: 100% New
- Application: Buildings And Projects
- Type: Fixed With Tower Head
- Max. Load: 8 T
- Jib Length: 60 M
- Tip. Load: 1.2 T
- Power supply: 380V/50Hz Or According To Client's Requirements
- Mast section: 1.835*1.835*2.5m (blcok Type)
- Electric Box: Schneider
- Power Supply: 380V/50Hz, 415V/50Hz, 220V/50Hz Or According To Clients Need
- Highlight: **8T QTZ6012 tower crane power cable, 60 meter tower crane building cable, Topkit tower crane power cable**

More Images

for more products please visit us on hycmtowercrane.com

Our Product Introduction

for more products please visit us on hycmtowercrane.com

Product Description

8T QTZ6012 Power Cable Kind Of Tower Cranes 60 meter Quotation Building Kren

Quick Details

This tower crane is an hammerhead with topkit head tower crane, includes foundation frame, mast sections (tower body), climbing system, slewing units, horizontal lifting jib / boom, counter-jib, tower head, operation cab, three mechanisms, electric system and safety device.
The max. Boom length is 60m which consist of every 6meters and minimum length is 30m
This tower crane freestanding height is 45m and max.height is 150m with more mast section and 5sets anchorages.
The max. Load capacity is 8t and tip load at the end jib is 1.2t.

Specification

Model		QTZ100(6012) Tower Crane
Working Radius (m)		60
Max. Load Capacity (T)		8
Tip Load (T)		1.2
Free standing height (m)		45
Max. Height with anchorages (m)		150
Mast Section dimension (m)		1.835×1.835×2.5, square steel 135×12mm
Hoisting Mechanism	Speed (m/min)	80/40/8.5 40/20/4.25
	Motor power (kw)	30/30
Slewing Mechanism	Speed (r/min)	0.6
	Motor power (kw)	2*3.7
Trolleying Mechanism	Speed (m/min)	40/20
	Motor power (kw)	3.3/2.2
Jacking-up System	Speed (m/min)	0.4
	Motor power (kw)	5.5
Total Power (kw)		46.2
Power Supply		380V/50Hz, 220V/60Hz or others

Our Service

------Quality Assurance
Good quality is assured by advanced manufacturing technology. And all products will be checked by our quality-control manager.
------Excellent Package
We provide standard, strong, protective package for our products to prevent it from outer damage.
------Warranty Assurance
For our tower crane, we provide 1 year warranty period and quick replace service.
------The Fastest Reply
Detailed information,specific model and price of products will be provided quickly after receiving inquiry.

Safety devices:
1) Hoist height limit
2) Over speed limit
3)Over load limit
4) Lifting moment limit
5) Slewing angle limit
6) Emergency stop button
7) Obstruction light (tip of jib, tower head)
8) Wind lock device.

Competitive Advantage

1. Focusing on tower crane exporting for 15 years;
2. Manufacturer's representative;
3. Preferential ex-factory price, excellent product quality and good after-sales service are our pursuit;
4. Our tower cranes had exported to more than 20 countries, such as Vietnam, Philippines, Indonesia, India, Sri Lanka, Cambodia, Russia, Kazakhstan, Brazil, Cyprus, Belgium, Madagascar and Algeria etc.

We are dedicated to provide you professional solutions with Aclass Service!

Pictures

emma1109@foxmail.com
HYCM

emma1109@foxmail.com
HYCM

No.218-1,Building 8, Comprehensive Building, Zone 8, Dongshan Garden, Shuangshan Street, Zhangqiu District, Jinan City, Shandong Province, China