

# TC6518 Kind of Tower Cranes Remote Control Max. Load 10T Building Material

# **Basic Information**

- Place of Origin:
- Brand Name:
- Certification:
- Model Number:
- Minimum Order Quantity:
- Price:

**Our Product Introduction** 

- Packaging Details:
- Delivery Time: 20 days after receiving the deposit or origin
- Payment Terms:
- Supply Ability:



## **Product Specification**

Condition:	100% New
<ul> <li>Application:</li> </ul>	Buildings And Projects
• Туре:	Fixed With Tower Head
• Max. Load:	10 T
<ul> <li>Jib Length:</li> </ul>	65 M
• Tip. Load:	1.8 T
<ul> <li>Power supply:</li> </ul>	380V/50Hz Or According To Client's Requirements
<ul> <li>Mast section:</li> </ul>	1.835*1.835*2.5m Or 2*2*3m
Electric Box:	Schneider
<ul> <li>Power Supply:</li> </ul>	380V/50Hz, 415V/50Hz, 220V/50Hz

According To Clients Need

China HYCM

1

LC TT, LC

containers.

10 sets per month

CE, ISO, GOST, CU-TR

\$122000-130700 per set

QTZ160(6518) Tower Crane

Naked packing, 6\*40'HQ or 7\*40;HQ



for more products please visit us on hycmtowercrane.com

### More Images



### **Product Description**

#### TC6518 Kind of Tower Cranes Remote Control Max. Load 10T Building Material

#### **Short Description**

The tower crane's lifting height is obviously increased thanks to its self-erecting by adding mast sections and wall attached function.

It is applicable for construction of different industrial, commercial, office, and civil building lower than 200m, and becomes an ideal service-building machine at home.

#### Specification

•	
Rated Lifting Moment (KN.M)	1600
Model	QTZ160(6518) Tower Crane
Max. Lifting Load (t)	10
Tip Load (t)	1.8
Max. Lifting Height (m)	200
Free standing height (m)	50
Rope length (m)	500
Span (m)	65
Working range (m)	3 to 60
Slewing speed (r/min)	0-0.6
Trolley peed (m/min)	0-60
Jacking-up speed (m/min)	0.4
Counter jib length (m)	14.6
Power supply	380V/50Hz or according to client's requirements
Power Capacity (kw)	61.5
Electric switch box	Schneider
Main Material (mm)	125*14 /two angle steel with rib
Mast section (m)	1.835*1.835*2.5 or 2*2*3m
Optional parts (if you need them, please let me know in advance)	Anemometer Air condition in cabin 3) Block box 4) Remote control

Application field: Building height up to 60 floors (200m), loading capacity up to 10t, jib length is 65m or short. If you have some special requirements, we will design new type of tower crane for you.

Abroad markets: The Middle East Regions, Southeast Asia, Africa, Russia, ect.

Certificate: ISO9001-2008, CE, GOST

Package: nude in 6\*40"HQ or 7\*40'HQ container

Payment terms: 30% in advance, 70% balance payment before shipment date

Delivery time: 30 workdays after receiving 30% advanced payment

Warranty: 12 months from the bill date (arrival of destination). And overseas service center is available.

Material: Q345 manganese steel

MOQ: 1 set (the more you buy, the cheap it is)

#### **Technical Features**

1) Advanced technical parameters, max. Radius is 65m, the static height is 50m, it can reach up to max. height 200m by adding mast sections and anchorages.

2) The complete crane adopts internationally well-received beautiful shape.

3) The crane features high working speed and excellent speed regulation performance.

4) The cabin is independently installed externally with good vision and large inner space, thus offering a good working environment for operators.

5) Equipped a set of safety devices so as to ensure the tower crane's reliable operation.

#### Pictures



