



Top Slewing Huge Hammer Head Tower Crane qtz7550 25T Load 75M Jib

Our Product Introduction

for more products please visit us on hycmtowercrane.com

Basic Information

- Place of Origin: China
- Brand Name: HYCM
- Certification: CE, ISO, GOST, CU-TR
- Model Number: QTZ500(7550) Tower Crane
- Minimum Order Quantity: 1
- Price: \$257700-276300 per set
- Packaging Details: Naked packing, 12*40'HQ containers.
- Delivery Time: 45 days after receiving the deposit or origin LC
- Payment Terms: TT, LC
- Supply Ability: 5 sets per month



Product Specification

- Condition: 100% New
- Application: Buildings And Projects
- Type: Fixed With Tower Head
- Max. Load: 25 T
- Jib Length: 75 M
- Tip. Load: 5.0 T
- Mast section: 2.5*2.5*6 M
- Electric Box: Schneider
- Power Supply: 380V/50Hz, 415V/50Hz, 220V/50Hz Or According To Clients Need
- Color: Yellow, Red Or According To Clients Needs



More Images



Product Description

Top Slewing Huge Hammer Head Tower Crane qtz7550 25T Load 75M Jib

Performance parameters

- Max. jib length: 75m
- Max. lifting capacity 25t
- Max. hoisting capacity at jib tip: 5.0t
- Max. lifting moment 50000 t.m
- Max. free-standing height: 73m
- Max. working height of anchored crane: 200m
- Types of tower crane: stationary crane with embedded outriggers, stationary crane with under-frame and mobile tower crane.

Specification

Foundation	Fixed angle or according to clients needs
Model	QTZ500(7550) Tower Crane
Freestanding height	73 meters
Max. height	200 meters
Max. radius	75 meters
Jib end load	5.0 t
Max. load	25 t
Drum capacity	600 meters
Lifting speed	0-35 and 0-70 m/min
Slewing speed	0-0.57 r/min
Trolley speed	0-60 m/min
Power line voltage	380V/50Hz (60Hz) or others
Counter weight	Steel-structured frame (without concrete)
Mast section	2.5 x 2.5 x 6m (split type)

Features

Durable, safe and low-maintenance cranes live up to the highest manufacturing standards. They are durable, operator-friendly, safe and have low maintenance requirements.

Quality materials for durability

Our components are traceable back to original premium-quality manufacturers, ensuring that they can easily be replaced when necessary. The quality of our components assure good resistance to fractures under conditions of high loading and low temperatures.

Quality steel mill-certified to European EN standards.

High-quality components from suppliers represented worldwide.

Protected: For safeguarding, all components are fitted into housing of the highest quality. Fully enclosed motors - IP55 - ensure long lasting motor insulation.

Easily identifiable: Cables and components are numbered or marked for easy identification, reducing maintenance time and costs.

Efficient: Virtually all internal electrical installation is done using multi-plug connections which reduces erection time.

Safety devices:

- 1): Hoist height limit
- 2): Over speed limit
- 3): Over load limit
- 4): Lifting moment limit
- 5): Slewing angle limit
- 7): Obstruction light (tip of jib, tower head)
- 8): Wind lock device.

The process features

1) Automatic submerged arc welding is adopted in the main section limbs and chord boom. It has high thermal efficiency, high penetration, high production efficiency, while reducing the pores and crack defects, increases the weld strength and the beautiful appearance.

2) We adopt carbon dioxide gas welding; it has heat concentrated, a small welding line, high strength and resistance to rust and crack. it can reduce stress and deformation, it has high strength and resistance to rust and crack.

3) Shot blasting is used for masts to strength the hardness of steel surface; enhance the paint adhesion and prolonging its life

Pictures





0086-18254159408



emma1109@foxmail.com



hycmtowercrane.com

No.218-1,Building 8, Comprehensive Building, Zone 8, Dongshan Garden, Shuangshan Street, Zhangqiu
District, Jinan City, Shandong Province, China