

QTP5515 Construction Tower Cranes Topless Types Of Power Line

Basic Information

Place of Origin: ChinaBrand Name: HYCM

Certification: CE, ISO, GOST, CU-TR
 Model Number: QTZ80(PT5515) Tower Crane

Minimum Order Quantity: 1

• Price: \$58900-62500 per set

Packaging Details: Naked packing, 6*40'HQ containers.

• Delivery Time: 20 days after receiving the deposit or origin

LC

• Payment Terms: TT, LC

• Supply Ability: 30 sets per month



Product Specification

Application: Buildings And ProjectsType: Fixed With Tower Head

Max. Load: 6 T
 Jib Length: 55 M
 Tip. Load: 1.5 T

• Power supply: 380V/50Hz Or According To Client's

Requirements

Mast section: 1.833*1.833*2.5m (Block Type)
Main Chord: 135*12mm (square Tube)



More Images



QTP5515 Construction Tower Cranes Topless Types Of Power Line

Description

- 1. This tower cranes are a modern form of balance crane that fixed to the ground on a concrete slab, tower cranes often give the best combination of height and lifting capacity and are used in the construction of tall buildings.
- 2. The base is then attached to the mast which gives the crane its height. Further the mast is attached to the slewing unit (gear and motor) that allows the crane to rotate.

On top of the slewing unit there are three main parts which are: the long horizontal jib (working arm), shorter counter-jib.

Specification

Model		QTZ80(PT5515) Topless Tower Crane
Working Radius (m)		55
Max. Load Capacity (T)		6
Tip Load (T)		1.5
Free standing height (m)		40
Max. Height with anchorages (m)		150
Mast Section dimension (m)		1.833×1.833×2.5, square steel 135×12mm
Hoisting Mechanism	Speed (m/min)	(a=2)80/40/8.5; (a=4)40/20/4.25
	Motor power (kw)	24/24/5.4
Slewing Mechanism	Speed (r/min)	0.6
	Motor power (kw)	2*3.7
Trolleying Mechanism	Speed (m/min)	40/20
	Motor power (kw)	3.3/2.2
Jacking-up System	Speed (m/min)	0.4
	Motor power (kw)	5.5
Total Power (kw)		34.8

Feature

- 1. For even higher performances, cranes offer new possibilities for operation: saving time and space.
- 2. Has reduced dimensions in space due to the slewing part without cathead or jib tie bars
- 3. Smaller overall height, erection operations at a reduced height
- 4. Easier overflying of obstacles on site (cranes, electricity lines, cables,..)
- 5. Jib configuration can be changed in the air during evolution of sites

Why choose us

- 1. A professional tower crane supplier in China with 15 years experience
- 2. Exported to more than 20 countries with ISO9001 & CE & GOST Certifications
- 3. Hydraulic self-climbing mechanism
- 4. Variable-frequency slewing mechanism
- 5. Varialbe-speed frequency PLC control System
- 6. Operation data display screen and Safety monitoring system (Black Box)
- 7. Various safety devices

Our Service

-----Quality Assurance

Good quality is assured by advanced manufacturing technology. And all products will be checked by our quality-control manager.

-----Excellent Package

We provide standard, strong, protective package for our products to prevent it from outer damage.

-----Warranty Assurance

For our tower crane, we provide 1 year warranty period and quick replace service.

-----The Fastest Reply

Detailed information, specific model and price of products will be provided quickly after receiving inquiry.

Photos





emma1109@foxmail.com 0086 18254159408

0086-18254159408

emma1109@foxmail.com

hycmtowercrane.com

No.218-1,Building 8, Comprehensive Building, Zone 8, Dongshan Garden, Shuangshan Street, Zhangqiu District, Jinan City, Shandong Province, China