

8 Tons Power Line QTP5515 Tower Crane 55M Boom Long Working Construction

Basic Information

- Place of Origin:
- Brand Name:
- Certification:
- Model Number:
- Minimum Order Quantity:
- Price:
- Packaging Details:
- Delivery Time:
- Payment Terms:
- Supply Ability:



Product Specification

| Application: | Buildings And Projects |
|-----------------------------------|-------------------------------|
| • Type: | Fixed With Tower Head |
| • Max. Load: | 8 T |
| Jib Length: | 55 M |
| • Tip. Load: | 1.5 T |
| Mast section: | 1.835*1.835*2.5m (Block Type) |
| Main Chord: | 135*12mm (square Tube) |
| Color: | Yellow Or Others |
| | |

China HYCM

1

LC

TT, LC

CE, ISO, GOST, CU-TR

\$63500-67500 per set

30 sets per month

containers.

QTZ80(PT5515) Tower Crane

Naked packing, 6*40'HQ+1*20'GP

20 days after receiving the deposit or origin



More Images



Product Description

8 Tons Power Line QTP5515 Tower Crane 55M Boom Long Working Construction

Performance parameters and technical indexes reach both domestic and international advanced level.

- a. Max. jib length: 55 m
- b. Max. lifting capacity: 8 t

c. Max. hoisting capacity at jib tip: 1.5 t

- d. Max. lifting moment: 800 KN.M
- e. Max. free-standing height: 45 m
- f. Max. working height of anchored crane: 150 m
- g. Types of tower crane: stationary crane and outside climbing type. Mobile and inner climbing type are available

Specification

| Туре | Topless or Flat top no head |
|--|---|
| Max. Lifting Load (t) | 8 |
| Tip Load (t) | 1.5 |
| Max. Lifting Height with anchorage (m) | 150 |
| Free standing height (m) | 45 |
| Rope length (m) | 400 |
| Span (m) | 55 |
| Working range (m) | 3 to 55 |
| Slewing speed (r/min) | 0.6 |
| Trolley peed (m/min) | 40/20 |
| Jacking-up speed (m/min) | 0.4 |
| Counter jib length (m) | 15.4 |
| Power supply | 380V/50Hz or according to client's requirements |
| Power Capacity (KW) | 46.2 |
| Electric switch box | Schneider |
| Hoisting speed (m/min) | (a=2)80/40/8.5; (a=4)40/20/4.25 |
| Mast section (m) | 1.833*1.833*2.5m (135*12mm square steel) |

Our advantage

- 1. 15 years of experience in supplying new external climbing tower crane with HYCM Brand.
- 2. Export to more than 20 countries with CE/ISO/GOST/CU-TR Certificates.
- 3. Stationary/Traveling and internal climbing type tower crane are available
- 4. Impeller blasting/rust protection paint

5. Advanced painting process

- 6. Strict and experience welding line
- 7. New designed mast, can be used to Internal and external climbing tower crane
- 8. Well known brand mechanism system, Schneider Electronic control system, Jjiangte and Jiuhe motor
- 9. Engineers available to service machinery overseas.

10. For warranty, it is 12 months from the B/L date. What's more, some free easy worn spare parts are provided together with the crane.

Photos





Jinan Avitt International Trade Co., Ltd-HYCM Tower Crane

♥ 0086-18254159408 ♥ e

emma1109@foxmail.com

bycmtowercrane.com

No.218-1,Building 8, Comprehensive Building, Zone 8, Dongshan Garden, Shuangshan Street, Zhangqiu District, Jinan City, Shandong Province, China