



## QTZ180 6518 Flat Head Tower Crane Inverter Control Box High Efficiency

Our Product Introduction

for more products please visit us on [hycmtowercrane.com](http://hycmtowercrane.com)

### Basic Information

- Place of Origin: China
- Brand Name: HYCM
- Certification: CE, ISO, GOST, CU-TR
- Model Number: QTZ180(PT6518) Tower Crane
- Minimum Order Quantity: 1
- Price: \$132500-140700 per set
- Packaging Details: Naked packing, 7\*40'HQ containers.
- Delivery Time: 25 days after receiving the deposit or origin LC
- Payment Terms: TT, LC
- Supply Ability: 10 sets per month



### Product Specification

- Application: Buildings And Projects
- Type: Fixed With Tower Head
- Max. Load: 10 T
- Jib Length: 65 M
- Tip. Load: 1.8 T
- Power supply: 380V/50Hz Or According To Client's Requirements
- Mast section: 2\*2\*3 M (split Type)
- Main Chord: 200\*20 Mm
- Highlight: QTZ180 flat head tower crane inverter, 6518 flat top tower crane control box, high efficiency tower crane inverter



### More Images



## Product Description

### QTZ180 6518 Flat Head Tower Crane Inverter Control Box High Efficiency

#### Performance parameters

- Max. jib length: 65m;
- Max. lifting capacity 10t;
- Max. hoisting capacity at jib tip:1.8t;
- Rated lifting moment: 1800 Kn.m;
- Max. freestanding height: 60m; Max. working height of anchored crane: 180m;

#### Specification

|                                 |                                     |                       |
|---------------------------------|-------------------------------------|-----------------------|
| Model                           | QTZ180 (PT6518) Topless Tower Crane |                       |
| Working Radius (m)              | 65                                  |                       |
| Max. Load Capacity (T)          | 10                                  |                       |
| Tip Load (T)                    | 1.8                                 |                       |
| Free standing height (m)        | 60                                  |                       |
| Max. Height with anchorages (m) | 200                                 |                       |
| Mast Section dimension (m)      | 2×2×3, angle steel 200×20mm         |                       |
| Hoisting Mechanism              | Speed (m/min)                       | (a=2)0-100; (a=4)0-50 |
|                                 | Motor power (kw)                    | 45                    |
| Slewing Mechanism               | Speed (r/min)                       | 0-0.6                 |
|                                 | Motor power (kw)                    | 2*5.5                 |
| Trolleying Mechanism            | Speed (m/min)                       | 0-60                  |
|                                 | Motor power (kw)                    | 5.5                   |
| Jacking-up System               | Speed (m/min)                       | 0.4                   |
|                                 | Motor power (kw)                    | 7.5                   |
| Total Power (kw)                | 61.5                                |                       |

#### FAQ

Q1: Will you help with installation and stuff training?

Yes, we will send engineers to you and guide the installation and train your workers.

Q2: How do you control the quality?

We insist the "Quality is priority" always pay attention to quality control from the very beginning to the end. You can also be reassured by our one-year warranty and ISO certificates.

Q3: Where is your factory located? How can I visit there?

Our factory is located in Zhangqiu city, Shandong province, China.

All our clients - from home and abroad are warmly welcome to visit us!

#### Safety Devices

- 3 obstacle lights
- Height limiter
- Slewing limiter
- Range/ trolley limiter
- Weight limiter
- Moment limiter
- Anemometer and block box (optional)

#### Advantage of Fixed Tower Crane

1. 15 years of experience in supplying new tower cranes.
2. Export to more than 20 countries with CE/ISO/GOST/CU-TR Certificates.
3. Mobile and internal climbing type tower cranes are also available.
4. Impeller blasting and rust protection painting with advanced painting process.
5. Strict and experienced welding line.
6. New designed mast, can be used to internal and external climbing tower crane.
7. Well known brand mechanism system, Schneider Electronic control system, Jjiangte or Jiuhe motor.
8. Engineers available to service machinery overseas.
9. For warranty: 12 months from the B/L date.

#### Photos



**Jinan Avitt International Trade Co., Ltd-HYCM Tower Crane**



0086-18254159408



emma1109@foxmail.com



hycmtowercrane.com

No.218-1, Building 8, Comprehensive Building, Zone 8, Dongshan Garden, Shuangshan Street, Zhangqiu District, Jinan City, Shandong Province, China