TC5008 Cat Head Top Slewing Crane Tower 50M Boom Lifting Jib 4t Max.load

Our Product Introduction

Basic Information

- Place of Origin: China
- Brand Name: HYCM TOWER CRANE
- Certification: CE, ISO, GOST, CU-TR
- Model Number: QTZ50(5008) Tower Crane
- Minimum Order Quantity: 1
- Price: $28200-29800 per set
- Packaging Details: Naked packing, 3*40'HQ containers.
- Delivery Time: 10 days after receiving the deposit or origin LC
- Payment Terms: TT, LC
- Supply Ability: 40 sets per month

Product Specification

- Condition: 100% New
- Application: Buildings And Projects
- Type: Fixed With Tower Head
- Max. Load: 4 T
- Jib Length: 50 M
- Tip. Load: 0.8 T
- Power supply: 380V/50Hz, 415V/50Hz, 220V/50Hz Or According To Clients Need
- Mast section: 1.6*1.6*2.2 M
- Main Chord: 160*12 Mm
- After Sale Service: Engineers Available To Service Overseas
- Highlight: **TC5008 top slewing tower crane**, **50M boom lifting jib crane**, **4t max load tower crane**

More Images

for more products please visit us on hycmtowercrane.com

Our Product Introduction

Product Description

TC5008 Cat Head Top Slewing Crane Tower 50M Boom Lifting Jib 4t Max.load

Shot Technicals
1. Model: QTZ50(TC5008) Topkit Tower Crane
2. Type: fixed and external climbing
3. jib length: 50m
4. tip load: 0.8t
5. max.laod: 4t
6.freestanding height: 29m

Overview
1. This type Tower Cranes with the “top head” also called Topkit tower crane, Cat Head tower crane, Kit Top tower crane ect.
2. This Small tower crane or mini tower crane used for lower story buildings construction, normally 5-15 lays.
3. This crane can save time on other jobsite duties by easily moving materials from one place to another.
4. They can be used in conjunction with other tower cranes at sites where space is confined

Specification

Model		QTZ50 (5008) Tower Crane
Type		Fixed
Working Radius (m)		50
Max. Load Capacity (T)		4
Tip Load (T)		0.8
Free standing height (m)		29
Max. Height with anchorages (m)		120
Mast Section dimension (m)		1.6×1.6×2.2, angle steel 160×12mm
Hoisting Mechanism	Speed (m/min)	(a=2) 64.15/32.57/7.0 (a=4) 32.14/15.60/3.5
	Motor power (kw)	15/15/4
Slewing Mechanism	Speed (r/min)	0.70/0.35
	Motor power (kw)	3.7
Trolleying Mechanism	Speed (m/min)	38.6/25.2
	Motor power (kw)	2.2/1.5
Jacking-up System	Speed (m/min)	0.4
	Motor power (kw)	4
Total Power (kw)		24.9
Power Supply		380V/50Hz or according to clients needs

Our Advantage
High quality
Raw material is the foundation of product and the first hurdle to guarantee quality. tower crane bulk purchase steel directly from big steel factories like Jinan steel, improve the safety of product.

First class components
First-class product composed by first-class components, insisted to use the first class components, such as Schneider electric element etc.

Safety protection
Completely safety protection devices improves the safety, weight limiters, adopt the advanced pull-ring structure from abroad, moment adopt bow-board mechanical type which can be used in severe wild environment.

Pictures

for more products please visit us on hycmtowercrane.com

Jinan Avitt International Trade Co., Ltd-HYCM Tower Crane

0086 18254159408 emma1109@foxmail.com hycmtowercrane.com

No.218-1,Building 8, Comprehensive Building, Zone 8, Dongshan Garden, Shuangshan Street, Zhangqiu District, Jinan City, Shandong Province, China