



qtz125 Tower Crane Hammer-head Type 10tons 6018 60m With Cabin

Our Product Introduction

Basic Information

- Place of Origin: China
- Brand Name: AVITT or others
- Certification: CE, ISO, GOST, CU-TR
- Model Number: QTZ125(6018) Tower Crane
- Minimum Order Quantity: 1
- Price: \$100500-116500 per set
- Packaging Details: Naked packing, 6*40'HQ or 7*40'HQ containers.
- Delivery Time: 20 days after receiving the deposit or origin LC
- Payment Terms: TT, LC
- Supply Ability: 20 sets per month



Product Specification

- Condition: 100% New
- Application: Buildings And Projects
- Type: Fixed With Tower Head
- Max. Load: 10 T
- Jib Length: 60 M
- Tip. Load: 1.8 T
- Power supply: 380V/50Hz Or According To Client's Requirements
- Mast section: 1.835*1.835*2.5m Or 2*2*3m
- Electric Box: Schneider
- Power Supply: 380V/50Hz, 415V/50Hz, 220V/50Hz Or According To Clients Need

Product Description

qtz125 Tower Crane Hammer-head Type 10tons 6018 60m With Cabin

Features

QTZ125(6018) fixed tower crane in Madagascar
 Fixed / stationary tower crane
 Max. load: 10ton
 Tip load: 1.8ton
 Jib length: 69m
 CE, ISO, GOST, CU-TR certificates

Specification

Model	QTZ125(6018)	
Working Radius (m)	60	
Max. Load Capacity (T)	10	
Tip Load (T)	1.8	
Free Height Under Hook (m)	50	
Max. Height with anchorages (m)	180	
Mast Section dimension (m)	1.835×1.835×2.5 or 2*2*3	
Hoisting Mechanism	Speed (m/min)	0-100 0-50
	Motor power (kw)	45kw
Slewing Mechanism	Speed (r/min)	0-0.6
	Motor power (kw)	5.5×2
Trolleying Mechanism	Speed (m/min)	0-60
	Motor power (kw)	5.5
Jacking-up System	Speed (m/min)	0.4
	Motor power (kw)	5.5
Total Power (kw)	61.5 (not includes jacking-up system)	
Power Supply	380V/50Hz	
Base type	Well shaped base/cross base/ base with ballast	
No. of containers	7 x 40'HQs	
Optional parts (if you need them, please let me know in advance)	1) Anemometer 2) Air condition in cabin 3) Block box 4) Remote control	

Main Features

This tower crane with tower head which connects with jib and counter-jib by tie bars, gives tower crane stronger structure and stable working condition. Besides, It's the most popular type at home and abroad with cheap cost.

Four Mechanisms (Hoisting mechanism, Slewing mechanism, trolleying mechanism and hydraulic climbing mechanism) work together to control the tower crane operation.

Equipped with full safety device to avoid over-weight loading, over-speed and over-torque, so that it is with good speed-control capacity, satisfactory operating stability and high work efficiency.

They can be widely used for construction of high-rise buildings, bridge and tower-like buildings.

Why choose us

1. A professional tower crane supplier in China with 15 years experience
2. Exported to more than 20 countries with ISO9001 & CE & GOST Certifications
3. Hydraulic self-climbing mechanism
4. Variable-frequency slewing mechanism
5. Variable-speed frequency PLC control System
6. Operation data display screen and Safety monitoring system (Black Box)
7. Various safety devices

Pictures



Jinan Avitt International Trade Co., Ltd-HYCM Tower Crane



0086-18254159408



emma1109@foxmail.com



hycmtowercrane.com

No.218-1, Building 8, Comprehensive Building, Zone 8, Dongshan Garden, Shuangshan Street, Zhangqiu District, Jinan City, Shandong Province, China

