



Small PT4010 Flat Top Tower Crane 40m Jib 4 ton Load Same Potain Steel

Our Product Introduction

Basic Information

- Place of Origin: China
- Brand Name: AVITT KANGTAI TOWER CRANE
- Certification: CE, ISO, GOST, CU-TR
- Model Number: PT4010 Tower Crane
- Minimum Order Quantity: 1
- Price: \$35600-45900 per set
- Packaging Details: Naked packing, 3*40'HQ containers per PT4010 tower crane
- Delivery Time: 20 days after receiving the deposit or origin LC
- Payment Terms: TT, LC
- Supply Ability: 200 sets per month



Product Specification

- Condition: 100% New
- Application: Buildings And Projects
- Type: Fixed With Tower Head
- Max. Load: 4 T
- Jib Length: 40 M
- Tip. Load: 1.0 T
- Power supply: 380V/50Hz Or According To Client's Requirements
- Mast section: 1.2*1.2*3m S24
- Electric Box: Schneider
- Steel Structure: Potain Type
- Highlight: **125 ton tower crane, high rise building crane, 65m jib tower crane**

for more products please visit us on hycmtowercrane.com

Product Description

Small PT4010 Flat Top Tower Crane 40m Jib 4 ton Load Same Potain Steel

Features

- 1) Working Radius (m): 40
- 2) Max. Load Capacity (T): 4
- 3) Tip Load (T): 1.0
- 4) Mast Section dimension (m): 1.2×1.2×3m S24

Specification

Rated Lifting Moment (KN.M)	400
Type	Fixed without tower head
Rated Loading Capacity (t)	4
Max. Lifting Load (t)	4
Tip Load (t)	1.0
Max. Lifting Height (m)	120
Free standing height (m)	27
Rope length (m)	320
Span (m)	40
Working range (m)	3 to 40
Slewing speed (r/min)	0.7/0.35
Trolley speed (m/min)	38.6/25.2
Jacking-up speed (m/min)	0.4
Counter jib length (m)	12.89
Power supply	380V/50Hz or according to client's requirements
Power Capacity (kw)	24.9
Electric switch box	Schneider
Hoisting speed (m/min)	(a=2) 64.15/32.57/7.0; (a=4) 32.14/15.60/3.5
Mast section (m)	1.2*1.2*3m S24

Advantage

Automatic impeller blasting and spraying assembly line
Adopt the world first-class automatic spraying assembly line. The large structure parts are dealt with impeller blasting before spraying. That remove steel surface oxides and welding spatters effectively, eliminates the internal stress producing in welding process, increases the parts' anti-figure strength and steel surface hardness, increases painting adhesion and prolong the service life of the product maximizes efficiency and saves energy.

Strict quality examination

The strict quality test, raw material test, test of welding, checking welding quality of appearance, assembly and adjustment of jib, tower head and pivot in factory.

We have professional packing person to pack and put the tower crane in the container or on to the truck.

Components

Mast: the main supporting tower of the crane. It is made of steel trussed sections that are connected together during installation.

Slewing unit: the slewing unit sits at the top of the mast. This is the engine that enables the crane to rotate.

Operating cabin: the operating cabin sits just above the slewing unit. It contains the operating controls.

Jib: the jib, or operating arm, extends horizontally from the crane. A "luffing" jib is able to move up and down; a fixed jib has a rolling trolley that runs along the underside to move goods horizontally.

Safety Device for hammerhead Tower Crane

1. 3 obstacle lights
2. Height limiter
3. Slewing limiter
4. Range/ trolley limiter
5. Weight limiter
6. Moment limiter
7. Anemometer and block box(optional)

Pictures



Jinan Avitt International Trade Co., Ltd-HYCM Tower Crane

☎ 0086-18254159408

✉ emma1109@foxmail.com

🌐 hycmtowercrane.com

No.218-1, Building 8, Comprehensive Building, Zone 8, Dongshan Garden, Shuangshan Street, Zhangqiu District, Jinan City, Shandong Province, China