



HGY24-3 Floor Concrete Placing Boom could inner climbing inside the buildings

Our Product Introduction

Basic Information

- Place of Origin: China
- Brand Name: AVITT ZHANGFAN OR OTHERS
- Certification: CE, ISO
- Model Number: HGY24 Floor Placing boom
- Minimum Order Quantity: 1
- Price: \$46400-47900 per set
- Packaging Details: Naked packing, 40'HC containers per set HGY24 Floor placing boom
- Delivery Time: 20 days after receiving the deposit or origin LC
- Payment Terms: TT, LC
- Supply Ability: 10 sets per month



Product Specification

- Condition: 100% New
- Application: Buildings And Projects
- Type: Fixed Inner Climbing
- Power: 18.5kw
- Speed: 0-0.25
- Work Height: 22.5m
- Concrete Conveying Pipe: $\Phi 125$
- Mast section Length: 10m*2
- Electric Box: CHNT Or Schneider
- Power Supply: 380V/50Hz, 415V/50Hz, 220V/50Hz Or According To Clients Need
- Highlight: QTZ6520 top slewing tower crane,
65m working boom tower crane,
topkit tower crane with head cost

Product Description

HGY24-3 Floor Concrete Placing Boom could inner climbing inside the buildings

Description

Max. boom length - 24 m;

Concrete pipe line (steel, DN125 mm), outer diameter of the and fitting on pipes - 148 mm

The High pressure flexible concrete hose with two and fitting (3000 mm) must be included in the delivery;

Support - outrigger (4 legs);

Remote control - wired remote control.

Specification

Model	HGY24-3	
Concrete conveying pipe (mm)	Φ125	
Horizontal reach (m)	24	
Work height (up to the hinge point of the arm root)	22.5m	
Boom Angle	1 section boom	0 °~ 90 °
	2 section boom	0 °~ 180 °
	3 section boom	0 °~ 180 °
Rotation	360 °	
Rotation speed	0~0.25 r/min	
Power	18.5KW	
System Pressure	32MPa	
Climbing method	Floor climbing	
Freestanding height (m)	22.5	
Control mode	Cable/Radio remote/Panel	
Power supply	380V/50Hz	
Wind speed	工作working	≤56 km/h
	非工作Non-working	≤72 km/h
Working environment temperature	-20 °C~40 °C	
Working altitude	≤1000m	
self weight	19000Kg	

Characteristics

The HGY concrete placing boom is a spreading equipment used in conjunction with concrete pumps for pouring concrete during construction, suitable for any concrete building such as buildings, bridges, roads, foundations, etc. The use of concrete placing boom can fully utilize the working efficiency of concrete pumps, improve pouring quality, and reduce labor intensity.

Advantage

1. Export to more than 20 countries with CE/ ISO/ GOST Certifications by skilled sales team.
2. Mobile and internal climbing type are also offering as new designed
3. High Quality control: blasting and rust protection painting with advanced painting process. Strict and experience welding line.
4. Well known hydraulic system and Electronic control system.
5. Engineers are available to service machinery overseas within 12 months warranty.
6. One set free easy-worn spare parts are provided with per set tower cranes.

Pictures



Jinan Avitt International Trade Co., Ltd-HYCM Tower Crane



0086-18254159408



emma1109@foxmail.com



hycmtowercrane.com

No.218-1,Building 8, Comprehensive Building, Zone 8, Dongshan Garden, Shuangshan Street, Zhangqiu District, Jinan City, Shandong Province, China

